1   110006   15-055-10084-0000

To: API NUMBER 15-   Completed 3-27-60
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION   C SW SW ¼, SEC.____16__,·T___21_S, R___33_W/EX
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202   660   feet from   S section line

TECHNICIAN'S PLUGGING REPORT   4620   feet from   E section line

Operator License # 5447   Lease Name Hyer "A"   Well #   2

Operator: Cities Service Oil & Gas Corp.   County   Finney   150.93
Name &
Address   3545 NW 58th Street   Well Total Depth   4644   feet

           Oklahoma City, OK 73112   Conductor Pipe: Size_____feet_____

                                             Surface Casing: Size 8 5/8 feet____316

Abandoned Oil Well___x___ Gas Well_____ Input Well_____ SWD Well_____ D&A_____

Other well as hereinafter indicated_____

Plugging Contractor_____DACO, Inc._____ License Number_____6416_____

Address_____Drawer 3010, Borger, TX 79007_____

Company to plug at: Hour: 9:30 am   Day:____19___ Month:____September Year:19__85___

Plugging proposal received from_____Jack Pointer_____

(company name)_____DACO_____(phone) 806-273-7321____

were: 4 1/2" at 4643' PBTD 4248' Perfs at 4286-4292', 4182-4185', Notch at 4578'

Spot cement through tubing with mud between plugs.

1st plug at 1900' with 50 sx cement - perforate at 1200' and spot 40 sx cement opposite

perfs. Pressure squeeze down 4 1/2" casing to get cement out perfs.

3rd plug shoot 4 1/2" off at 975' and spot 35 sx cement- pull casing to 350'

4th plug spot 35 sx cement at 350' pump mud to 40' - 5th plug at 40' with 10 sx cement

                      Plugging Proposal Received by__Don C. Ubel_____
                                                         (TECHNICIAN)

Plugging Operations attended by Agent?: All____X_____ Part_____ None_____

Operations Completed: Hour: 4:00 pm Day:____19___ Month:___September_ Year:19__85__

ACTUAL PLUGGING REPORT_1st plug at 1900' with 40 sx cement, perforated at 1200' and spotted

35 sx cement. 3rd plug at 776' with 35 sx cement, 4th plug at 367' with 35 sx cement, 5th

plug at 40' with 15 sx cement - cemented to surface.

Remarks:___Used common cement by Daco. Recovered 776' 4 1/2" casing._____
               (If additional description is necessary, use BACK of this form.)

INVOICED

I did xxxxxxx observe this plugging.   RECEIVED
                                      STATE CORPORATION COMMISSION
DATE 9-30-85   09-27-85   Signed_____James R Kapp_____
                                         SEP 27 1985   (TECHNICIAN)
INV. NO. 10281
                                      CONSERVATION DIVISION   FORM CP-2/3