TO:

STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-185-21562-00-00
Spot: CE2NENE Sec/Twnshp/Rge: 23-22S-12W
4620 feet from S Section Line, 330 feet from E Section Line
Lease/Unit Name: BYER Well Number: 1
County: STAFFORD Total Vertical Depth: 3654 feet

Operator License No.: 5030
Operator Name: VESS OIL CORPORATION
Address: 8100 E. 22ND N. BLDG. 300
WICHITA, KS 67226 10/27

Conductor Pipe: Size feet:
Surface Casing: Size 8.625 feet: 278 WITH 250 SX CMT
Production: Size 4.5 feet: 3652 WITH 175 SX CMT
Liner: Size feet: 118.76

Well Type: OIL UIC Docket No: Date/Time to Plug: 10/27/2000 12:00 PM

Plug Co. License No.: 31529 Plug Co. Name: MIKE'S TESTING & SALVAGE, INC.

Proposal Rcvd. from: MONTE ANDREWS Company: MIKE'S TESTING & SALVAGE, INC. Phone: (316) 938-2537

Proposed Plugging Method: SAND TO 3600' AND 4 SX CMT. 1ST PLUG AT 660' WITH 50 SX CMT. 2ND PLUG AT 310' WITH 50 SX CMT. 3RD PLUG AT 40' WITH 20 SX CMT. USE 10 SX GEL FOR GEL SPACER.

Plugging Proposal Received By: STEVE MIDDLETON WitnessType: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 10/27/2000 1:00 PM KCC Agent: STEVE PFEIFER

Actual Plugging Report:

ARBUCKLE OPEN HOLE AT 3652-54'. SAND BACK TO 3480' AND PUT 4 SX CMT ON TOP OF SAND BRIDGE THROUGH DUMP BAILER. PUMP DOWN 8 5/8" SURFACE PIPE WITH 300# HULLS - 10 SX GEL - 50 SX CMT - 10 SX GEL - 100# HULLS - 8 5/8" WIPER PLUG & 100 SX CMT. MAXIMUM PRESSURE 600#. SHUT IN PRESSURE 250#.

RECEIVED
STATE CORPORATION COMMISSION
NOV 2 2000
11-2-00
CONSERVATION DIVISION
Wichita, Kansas

Remarks: USED 60/40 POZMIX 6% GEL BY ALLIED. RECOVERED 840' OF 4 1/2' CASING.

Plugged through: CSG

District: 01

Signed Stephen J. Pfeifer
(TECHNICIAN)

INVOICED
DATE 11/3/00
INV. NO. 2001060933

OCT 31 2000

Form CP-2/3