

15-185-01627-0001

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

OR
FORMATION PLUGGING RECORD

Strike out upper line
when reporting plug-
ging of formations.

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bitting Building
Wichita, Kansas

Stafford County, Sec. 28 Twp. 23 Rge. 12W (E) (W)

Location as "NE $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$ " or footage from lines NW SE SW

Lease Owner The Texas Company

Lease Name M. Gerdes Well No. 3

Office Address Box 2420, Tulsa, Oklahoma

Character of Well (completed as Oil, Gas or Dry Hole) Oil

Date well completed 9-23-41 19. 41

Application for plugging filed October 8 19. 45

Application for plugging approved October 16 19. 45

Plugging commenced December 5 19. 45

Plugging completed December 15 19. 45

Reason for abandonment of well or producing formation Not producing commercial quantity of oil.

If a producing well is abandoned, date of last production July 31 19. 44

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well H. W. Kerr - Great Bend, Kansas

Producing formation Depth to top Bottom Total Depth of Well 3860' Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
				5 1/2" 17#	3858'	946'
				10-3/4 29#	280'	None

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Filled hole with mud up to 250' of top. Made rock bridge from 250' to 240', then run 15 sacks cement which filled hole up to 210' of top. Run mud from 210' to 20' of top. Run 10 sacks cement which filled hole up to the top of hole.

28 23 12W
28 25



(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to The Texas Company Producing Department
Address Box 1801, Wichita, Kansas

STATE OF Kansas, COUNTY OF Sedgwick, ss.

M.C. Harrell 614 Bitting Bldg. (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) M.C. Harrell

Box 1801, Wichita, Kansas (Address)

SUBSCRIBED AND SWORN to before me this 18 day of January, 19 46

Lurpha W. Butts Notary Public.

My commission expires 1949 - Aug. 26

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas


15-185-01627-000P

THE TEXAS CO.
M. Gerdes No. 3.

SEC. 28 T. 23 R. 12W
NW SE SW

Total Depth. 3860'
Comm. 8-30-41 Comp. 9-23-41
Shot or Treated.
Contractor. Warren & Bradshaw Drlg.
Issued. 10-25-41 Rotary O-3858
Cable 3858-60

County. Stafford



CASING:
10 3/4" 286' Cem.
5 3/8" 3858' Cem.

Elevation.

Production. Pot. 15 B. Min.

Figures Indicate Bottom of Formations.

sand	120
shale red, gyp, shells	235
shale & red bed	355
red bed	375
red bed, sand, shale	975
shale & shells	1515
lime brkn	2030
limo hrd	2105
lime brkn & shale	2350
shale & limo	2700
lime brkn	2785
shale & shells	2820
shale & limo	2885
sand	2911
shale	2925
lime	2940
shale	2983
limo & shale	3192
lime hrd	3212
lime	3297
lime & shale	3428
lime	3495
lime & chert	3531
lime	3538
shale & lime	3581
shaly shale	3590
lime hrd	3602
lime	3708
lime w/ chert	3732
lime & chert	3776
chert	3795
shale & lime	3822
dolomite	3827
shale	3858
limo brkn	3860
Total Depth.	

Perforated pipe from 3846 to 58 -
36 holes & from 3822 to 34 - 36
holes
Jetted 1000 Gals. Acid - and 500
Gals. Acid before and after jet
Took swb test and established 15
bbl. min. well.

Top Arbuckle 3853

28 23 12W
28 25

