X	2	
V		

	770190	API NUMBER 15- 185-22,152	-0000 Y
To: STATE CORE	PORATION COMMISSION 16	55' S	
CONSERVAT	ION DIVISION - PLUGGING SECTION $_{ m NE}$ ado derby building	SW_NW, SEC10, T_2	2\$, R12_₩/E
WICHITA,	KANSAS 67202	feet from	m S section line
TECHNICIAI	N'S PLUGGING REPORT	4290feet from	m E section line
Operator i	License # 5030	Lease Name Spangenberg	Well # 1
	PV Properties, Inc.	CountyStafford_	114.24
_	400 North Woodlawn, Suite 101	Well Total Depth 3	
Vadi 422	Wichita, KS 67208	Conductor Pipe: Size	
	· ·	Surface Casing: Size 8 5/	
	Oll WellGas Well		
	t as hereinafter indicated		
	Contractor L. D. Drilling, Inc.		umber <u>6333</u>
Address	R. R. 1, Box 183-B, Great Bend,	KS 67530	
Company t	o plug at: Hour: 6:00 am Day: 1	6 Month: January	Year:19 <u>85</u>
Plugging	proposal received fromD	on Pope	····
(company	name) L. D. Drilling	(ph	one)316-793-3051
	fill hole with heavy mud and spot		
	at 660' with 40 sx cement	CONCIDE FILL WIRE COLOR FOR FILE FOR	
	at 300' with 40 sx cement		
	solid bridge		
,	hulls -'plug at 40' cement to s		
orn brug i	to circulate rat hole with 15 sx c		T
	Plugging Prope	osal Received by Richard W. (TE	Lacey ECHNICIAN)
Piugging	Operations attended by Agent?: A	II Part	None y
	as Completed: Hour: 7:30 am Day:1		
•			
	UGGING REPORT 1st plug at 660' wit	<u> </u>	
sx cement,	, 3rd & 4th plugs - solid bridge -	nulls - plug at 40 cemen	
with 10 s	k cement, 5th plug to circulate ra	t hole with 15 sx cement.	RECEIVED TATE CORPORATION COMMI
			JAN 2 3 1985
		1-23-85	CONSERVATION DIVISION
			Wichita, Kansas
Remarks:	Used 60/40 Pozmix 2% gel 3% cc by	Halliburton necessary, use BACK of this	forma)
	dTd not) observe this plugging.		
1-2	8-85	Signed Richard W.	Lace, Sel
1,64	57	(TECHNIC)	AN)
). <u>O 20</u>			FORM CP-2