

1 090384

12-23

API NUMBER 15-055-21,263-0000

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

NE SW NW, SEC. 32, T 22 S, R 30 W/EX

3630 feet from S section line

2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5886

Lease Name Tarpley "A" Well # 1-32

Operator: Chief Drilling, Inc.

County Finney

Name & Address 120 S. Market, Ste. 300

Well Total Depth 4860 157.95 feet

Wichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 299

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Chief Drilling, Inc. License Number 5886

Address 120 S. Market, Ste. 300, Wichita, KS 67202

Company to plug at: Hour: 8:15 p.m. Day: 23 Month: 12 Year: 1993

Plugging proposal received from Harold

(company name) Chief Drilling, Inc. (phone) 316-262-3791

Work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2061'

1st plug at 2070' with 50 sx cement, 2nd plug at 1270' with 80 sx cement,

3rd plug at 330' with 50 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 11 p.m. Day: 23 Month: 12 Year: 19 93

ACTUAL PLUGGING REPORT 1st plug at 2070' with 50 sx cement,

2nd plug at 1270' with 80 sx cement,

3rd plug at 330' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 1/2# floseal by Allied.

(If additional description is necessary, use BACK of REPORT)

(Witness) observe this plugging.

INVOICED

DATE 1-6-94

INV. NO. 39626

Signed \_\_\_\_\_

RECEIVED STATE CORPORATION COMMISSION  
JAN 03 1994  
TECHNICAL CONSERVATION DIVISION  
Wichita, Kansas

EFFECTIVE DATE: 12-12-93

State of Kansas 15-055-21,263-0000

FORM MUST BE TYPED

FORM MUST BE SIGNED

ALL BLANKS MUST BE FILLED

DISTRICT # 1

NOTICE OF INTENTION TO DRILL

SEA? Yes No

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 12-10-93 month day year

Spot NE SW NW Sec 32 Twp 22S Rg 30 East X West

OPERATOR: License # 5886
Name: Chief Drilling, Inc.
Address: 120 S. Market, #300
City/State/Zip: Wichita, KS 67202
Contact Person: Douglas W. Thimesch
Phone: 316 262-3791
FAX 262-4504

3630 FSL feet from South / North line of Section
2970 FEL feet from East / West line of Section
IS SECTION X REGULAR IRREGULAR?

(NOTE: Locate well on the Section Plat on Reverse Side)

CONTRACTOR: License # 5886
Name: Chief Drilling, Inc.

County: Finney
Field Name: Tarpley "A" Well #: 1-32

Well Drilled For: Well Class: Type Equipment:
Oil Enh Rec Infield Mud Rotary
Gas Storage X Pool Ext. Air Rotary
DUWO Disposal Wildcat Cable
Seismic: # of Holes Other

Is this a Prorated/Spaced Field? yes X no

Target Formation(s): Mississippi

Nearest lease or unit boundary: 330

Ground Surface Elevation: approx. 2853 gr feet MSL

Water well within one-quarter mile: yes X no

Public water supply well within one mile: yes X no

Depth to bottom of fresh water: 110

Depth to bottom of usable water: 1250

Surface Pipe by Alternate: 1 X 2

Length of Surface Pipe Planned to be set: 300

Length of Conductor pipe required: none

Projected Total Depth: 4880

Formation at Total Depth: Mississippi

Water Source for Drilling Operations:

well farm pond X other

If DUWO: old well information as follows:
Operator:
Well Name:
Comp. Date: Old Total Depth:

DNR Permit #:

Will Cores Be Taken?: yes X no

If yes, proposed zone:

Directional, Deviated or Horizontal wellbore? yes X no

If yes, true vertical depth:

Bottom Hole Location:

Exp. 6/7/94

AFFIDAVIT

300' Alt. II Req.

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

It is agreed that the following minimum requirements will be...

Pusher: Harold
SPUD DATE: 12-11-93 INIT. CA
LENGTH SURFACE PLANNED: 300+
RESERVE PIT STATUS- REMOVE FLUID LINED
RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 8 1/2" @ 290' CONDUCTOR
ANHYDRITE T-B-2061 ELEVATION
TD 4860 FORMATION
RAN PIPE @ DV TOOL ALT II DONE
Arbuckle Plug @ Ft. W/ SX
Hug./Council @ Ft. W/ SX
Anhydrite Base @ 2070 Ft. W/ 50 SX
1/2 Base Anyh. @ 1270 Ft. W/ 80 SX
1/2, 1/2 Plug @ Ft. W/ SX
Bottom Surface @ 330 Ft. W/ 50 SX
40' Plug @ 40 Ft. W/ 10 SX
RAT HOLE CIRC/W 5 SX MOUSE HOLE W/ 10 SX
WATER WELL Filter SX (Irr. Well Pond Hauling)
TECHNICAL RECEIVED
OPERATION DATE 12-23-93
COMPLETION TIME 8:15 (AM/PM) DATE 12-23-93
COMPLETION TIME 11:00 (AM/PM) DATE 12-23-93
CEMENT COMPANY Allied