

1 040050

2-2-88

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 185-21,670-0000
W SW SW NE SEC. 24, T 22 S, R 12 W/E

TECHNICIAN'S PLUGGING REPORT

2970 feet from S section line
2410 feet from E section line

Operator License # 6039

Lease Name Heyen Well # 2

Operator: L.D. Davis dba/L.D. Drilling, Inc.
Name & Address: RR 1, Box 183B
Great Bend, KS 67530

County Stafford 118.66'

Well Total Depth 3651 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 250

Abandoned Oil Well Gas Well _____ Input Well _____ SWD Well _____ D&A _____

Other well as hereinafter indicated _____

Plugging Contractor Kelso Casing Pulling, Inc. License Number 6050

Address Box 347, Chase, KS 67524

Company to plug at: Hour: 4:15 p.m. Day: 2 Month: 2 Year: 19 88

Plugging proposal received from Clay Duntz

(company name) Kelso Casing Pulling, Inc. (phone) 316-938-2457

were: 4 1/2" at 3649' Open hole at 3649-51'

1st plug sand back to 3600' and dump 4 sx cement on top of sand through bailer,

2nd plug pump 4 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8" wiper plug and pump 100 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 4:45 p.m. Day: 2 Month: 2 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug sanded back to 3600' and dumped 4 sx cement on top of sand through bailer,

2nd plug pumped down 8 5/8" with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,

100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement

STATE CORPORATION COMMISSION
FEB 08 1988

Maximum pressure 600 psi and shut in 50 psi.

Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2520' of 4 1/2" casing.
(If additional description is necessary, use BACK of this form.)

INVOICED (do not check) observe this plugging.

DATE 2-10-88

INV. NO. 19806

Signed Stephen J. Pfeifer (TECHNICIAN)