

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission  
Conservation Division  
211 North Broadway  
Wichita, Kansas

FILE NO. 103-33

LOCATION SW SE NE

SEC. 31 TWP. 21 RGE. 15W

Dry Hole \_\_\_\_\_ Abandoned Oil Well Oil Abandoned Gas Well \_\_\_\_\_

I have this date completed supervision of plugging of:

Well No. 1 Lease Hauser

Operator Petroleum, Inc. Address 311 East Third, Wichita, Kansas

Field \_\_\_\_\_ County Pawnee

Total Depth 3962 Feet.

Plugging Contractor Morgan Pipe Pulling Company

Plugging Contractor's License No. 43

Address 108 West Second Street, Hutchinson, Kansas  
(Describe briefly the manner in which the well was plugged)

Drilled cement out to a total depth of 3,941.5'

Filled hole with crushed rock from 3,941.5' to 3,999' and

placed five sacks cement from 3,999' to 3,865'. Globe Oilwell

Cementing, Inc. pumped down 20 sacks of Controlbar to kill

DDakota water flow, and then pumped in cement from 800' to

125'. Filled surface pipe with sand and capped with cement.

STATE CORPORATION COMMISSION  
MAY 9 X 1955

5-9-55  
W. L. Rivers  
District Conservation Agent

PLUGGING  
STATE CORPORATION COMMISSION  
Wichita, Kansas  
FILE SEC 21 T 21 R 15W  
BOOK PAGE 103 LINE 33

DATE April 19, 1955