15-185-12002-0002 <sup>1</sup> 120320 Docket #E-15,937 API NUMBER 15-Drill Completion Date 7/19/67 STATE CORPORATION COMMISSION SE NW NW SEC. 9 . 7 22 S. R 13 W/E CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING feet from 4290 S section line WICHITA, KANSAS 67202 feet from TECHNICIAN'S PLUGGING REPORT E section line 429A Operator License # 6588 Lease NameSoeken-BesthornWell / 3 Stafford County Operator: Woodman-Iannitti Oil Company &emak P.O. Box 308 Well Total Depth 3615 feet Address Conductor Pipe: Size feet Great Bend, KS 67530 Surface Casing: Size 8 5/8 feet 288 Abandoned Oll Well Gas Well\_\_\_\_\_ Input Well\_\_\_\_ SWD Well D&A Other well as hereinafter indicated License Number 5111 Plugging Contractor Rockhold Engineering Address P.O. Box 698, Great Bend, KS 67530 Company to plug at: Hour: 10 a.m. Day: 5 Month: 10 Year:19 89 Plugging proposal received from James Rockhold (company name) Rockhold Engineering (phone)316-792-2506 were: 5½" at 3614' PBTD 3557' Perfs at 3520-27' 5½" casing squeezed from 1386-0' w/650 sx cement, cement at bradenhead 1st plug pump in  $5\frac{1}{2}$ " casing with 200 lbs. hulls, 50 sx cement, 20 sx gel, and 75 sx cement with hulls mixed with all material. \_ 10-12-89 Duane Rankin Plugging Proposal Received by None Chical Plugging Operations attended by Agent?: All X Part Operations Completed: Hour: 11 a.m. Day: 5 Month: 10 ACTUAL PLUGGING REPORT 1st plug pumped into 51/2" casing with 200 lbs. hulls,50 sx cement, 20 sx gel. 75 sx cement, 300 lbs. hulls mixed in gel and cement. Pumping pressure 0-1000 psi and shut in 700 psi.

Remarks: Used 60/40 Pozmxi 6% gel by B.J. Titan. No casing recovery. (if additional description is necessary, use BACK of this form.)

Van Salass observe this plugging.

Signed