

To:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-145-20978-0000

Hwy Sec. 12, T 21 S, R 16 W/E  
SW 1/4 NW feet from N/S section line  
\_\_\_\_\_ feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6393

Lease Name Ph 10 Hwy Well # B-1

Operator: Brougher Oil Co  
Name & Box 1367 Great Bend Ks  
Address 67530

County Powder

Well Total Depth 3800 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 970' 4786

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Rock Hold Eng Inc License Number 5111 tag 93

Address PO Box 698 Great Bend Ks

Company to plug at: Hour: 9:00am Day: 25 Month: Jan Year: 1983

VERBAL PLUGGING ORDERS GIVEN TO Pulley

(company name) Rock hold Eng. Inc (phone) \_\_\_\_\_

were: 5 1/2 set at 3795 to 125 sy cement. Top Perf 3793-95-  
Sand back to 3740. 5 sy cement with foiler Recovered  
2900' of 5 1/2 squeezed well with 3 Halls- 50  
sy cement. 30 sy gel. 1 sy Hull. Released plug 120 sy  
cement. 50.50 sy 49 gel 29 cc

Signed J. M. Trub  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: \_\_\_\_\_ Day: 25 Month: Jan Year: 1983

ACTUAL PLUGGING REPORT Squeezed well with 3 54-Halls 50  
sy cement. 30 sy gel. 1 sy Halls. Released plug 120  
sy cement may press. 1000# shot in 1000#

Remarks: Control by Halliburton

I hereby certify that the above plugging instructions were given as herein stated and that I (did / did not) observe this plugging.

INVOICED  
DATE 2-7-83  
INV. NO 2338-4

RECEIVED  
STATE CORPORATION COMMISSION  
JAN 31 1983  
CONSERVATION DIVISION  
Wichita, Kansas

Signed J. M. Trub  
(TECHNICIAN)