

1 050557

R

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 145-21,208-0000

NW NE SE, SEC. 25, T 21 S, R 15 WXX
2310 feet from S section line
990 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5215
Operator: Lee Phillips Oil Company
Name & Address: 125 North Market, Suite 1532
Wichita, KS 67202

Lease Name Clarke Well # 1
County Pawnee 123.60
(Viola)
Well Total Depth 3803 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 902

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor JW Drilling, Inc. License Number 5137

Address 200 E. First, Suite 500, Wichita, KS 67202

Company to plug at: Hour: 2:00 am Day: 24 Month: June Year: 19 85

Plugging proposal received from Bill Roach

(company name) J.W. Drilling (phone) 316-26-35705

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 940'

- 1st plug at 940' with 50 sx cement
- 2nd plug at 320' with 40 sx cement
solid bridge
- 3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement
- 5th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by Richard W. Lacey
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4:00 am Day: 24 Month: June Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 940' with 50 sx cement, 2nd plug at 320' with 40
sx cement, 3rd & 4th plugs - solid bridge - hulls - plug at 40' -- cement to surface
with 10 sx cement, 5th plug to circulate rat hole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

JUL 01 1985

7-1-85

CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Halliburton.
(if additional description is necessary, use BACK of this form.)

INVOICED

(check and init) observe this plugging.

DATE 7-12-85

Signed Richard W. Lacey
(TECHNICIAN)

INV. NO. 8913