


DISTRICT CONSERVATION AGENT'S REPORT



TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. \_\_\_\_\_

LOCATION SE  
21W-7E-SE

SEC. 1 TWP. 21 RGE. 16W

Dry Hole \_\_\_\_\_ Abandoned Oil Well X Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 3 Lease Smith - "B"

Operator Ben F. Brack Co., Inc. Address 7310 Brown Bldg. Wichita - Kans.

Field \_\_\_\_\_ County Rawl

Total Depth 3780 Feet.

(Describe briefly the manner in which the well was plugged)

Surface Pipe 8 1/2" - 265 ft. Circulated with cement  
5 1/2" casing set at 3770 ft. Cemented with 150 sacks cement  
Plugged back to 3770 ft. with chat - Dumped 5 sacks  
of cement at 3770 ft. - Shot off & Pulled the 5 1/2" casing -  
Pumped in Plug & 120 sacks of cement - Filling  
hole from 400 ft to the surface with cement.  
Cement Pumped in by Halliburton

RECEIVED 11-6-50  
STATE CORPORATION COMMISSION

NOV 6 - 1950

C. W. Stouck  
District Conservation Agent  
Wichita, Kansas

Date 11-4-50

**PLUGGING**  
FILE SEC. 1 T 21 R 16W  
BOOK PAGE 40 LINE 38