

To: 1 060169  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

6-16 API NUMBER 15- 185-22,909-0000  
N/2 NW NE, SEC. 23, T. 23 S, R. 14 W/E

TECHNICIAN'S PLUGGING REPORT

Operator License # 5058  
Operator: Griggs Oil, Inc.  
Name &  
Address 100 N. Main, Ste. 1010  
Wichita, KS 67202

330 feet from N ~~S~~ section line  
1980 feet from E section line  
Lease Name Cornwell Well # 1-23  
County Stafford  
Well Total Depth 4055 131.78 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 277

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sterling Drilling, Inc. License Number 5142

Address P.O. Box 129, Sterling, KS 67579

Company to plug at: Hour: 10 a.m. Day: 16 Month: 6 Year: 19 93

Plugging proposal received from Vaughn Thompson

(company name) Sterling Drilling, Inc. (phone) 316-278-2131

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 815-45'

- 1st plug at 875' with 50 sx cement,
- 2nd plug at 310' with 50 sx cement,
- 3rd plug at 40' with 10 sx cement,
- 4th plug to circulate rathole with 15 sx cement

Plugging Proposal Received by Case Morris  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 12:30 p.m. Day: 16 Month: 6 Year: 19

ACTUAL PLUGGING REPORT 1st plug at 875' with 50 sx cement,

- 2nd plug at 310' with 50 sx cement,
- 3rd plug at 60' with 15 sx cement,
- 4th plug to circulate rathole with 15 sx cement.

6-17-93

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

**INVOICED**  
If (check) did not observe this plugging.

DATE 6-22-93

INV. NO. 37978

Signed Case Morris  
(TECHNICIAN)

RECEIVED  
STATE CORPORATION COMMISSION

JUN 17 1993  
CONSERVATION DIVISION  
Wichita, Kansas

EFFECTIVE DATE: 6-2-93

DISTRICT 1  
STATE 17

State of Kansas  
NOTICE OF INTENTION TO DRILL 185-22,909-0000

Must be approved by the K.S.C. five (5) days prior to commencing well

FORM C-1 7/9  
FORM MUST BE TYPE  
FORM MUST BE SIZED  
ALL BLANKS MUST BE FILLED

Expected Spud Date 6 1 93  
month day year

C. N/2 NW NE Sec 23 Twp 23 S. Rg 14 E. 14

OPERATOR: License # 5058  
Name: Griggs Oil, Inc.  
Address: 100 N. Main, Suite 1010  
City/State/Zip: Wichita, KS 67202  
Contact Person: James G. Collins  
Phone: (316) 267-7779

330 feet from South / North line of Section  
1980 feet from East / West line of Section  
IS SECTION X REGULAR

CONTRACTOR: License # 5142  
Name: Starling Drilling, Inc.

(NOTE: Locate well on the Section Plat on Reverse Side  
County: Stafford  
Lease Name: Cornwell Well #: 1-23  
Field Name: Alan  
Is this a Prorated/Spaced Field? yes no  
Target Formation(s): LKC/Arbuckle  
Nearest lease or unit boundary: 330'  
Ground Surface Elevation: 1922 feet MSL  
Water well within one-quarter mile: yes no  
Public water supply well within one mile: yes no  
Depth to bottom of fresh water: 100  
Depth to bottom of usable water: 225  
Surface Pipe by Alternate: 1 2  
Length of Surface Pipe Planned to be set: (300) 260'  
Length of Conductor pipe required: N/A  
Projected Total Depth: 4000  
Formation at Total Depth: Arbuckle  
Water Source for Drilling Operations:  
X well farm pond other  
OSR Permit #: Applied FOR  
Will Cores be Taken? yes no  
If yes, proposed zone: 260' Alt. I req.

Well Drilled For: Well Class: Type Equipment:  
X Oil ... Enh Rec ... Infield ... Mud Rotary  
... Gas ... Storage ... Pool Exp. ... Air Rotary  
... OWD ... Disposal ... Wildcat ... Cable  
... Seismic: ... # of Holes ... Other  
If OWD: old well information as follows:  
Operator:  
Well Name:  
Comp. Date: Old Total Depth:

Directional, Deviated or Horizontal wellbore? yes X no  
If yes, true vertical depth:  
Bottom Hole Location:

Exp. 11/28/93  
The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.  
It is agreed that the following minimum requirements will be met:

- 1. Notify the appropriate district office prior to spudding of well;

Pusher Vaughn, Thayer  
SPUD DATE 6-9-93 INIT. R.L.  
LENGTH SURFACE PLANNED 260  
RESERVE PIT STATUS- REMOVE FLUID LINED  
after salt sect. bbls. when done bbls.  
RATHOLED AHEAD? Y N SIZE HOLE  
SURFACE PIPE 8 1/2 @ 277 CONDUCTOR  
ANHYDRITE T- 8 1/2 B- 545 ELEVATION  
TD 4055 FORMATION Arbuckle  
RAN PIPE @ DV TOOL ALT II DONE  
SX SX Y N  
Arbuckle Plug @ Ft. W/ 40 SX NO  
Hug./Council @ Ft. W/ SX  
Anhydrite Base @ 875 Ft. W/ 50 SX  
1/2 Base Anyh. @ Ft. W/ SX  
1/2, 1/2 Plug @ Ft. W/ SX  
Bottom Surface @ 310 Ft. W/ 50 SX  
40' Plug @ 440 Ft. W/ 15 SX  
RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ SX  
WATER WELL SX (Irr. Well Pond  
Hauling  
ECHNICIAN CM DATE 6-14-93  
TYPE OF CEMENT 3160/40 670  
STARTING TIME 10:00 AM DATE 6-16-93  
COMPLETION TIME 12:30 (AM/PM) DATE 6-17-93  
WICHITA DIVISION  
KANSAS  
REGULATORY DIVISION  
PERMITTING  
COMMISSION  
WATER DIVISION  
KANSAS  
WICHITA