

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

15.009.00323.00.01
API NUMBER 15- -

TECHNICIAN'S PLUGGING REPORT

Operator License # 5258

Operator: Messman-Prinehart, Corp.
Name & Address 1432 K.S.B.&T. Bldg.
Wichita, Ks. 67202

SE, Sec. 16, T 19 S, R 14 (W)E

990 feet from N/S section line

660 feet from W/E section line

Lease Name Essmiller A Well # 1

County Barton

Well Total Depth 3596 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8" feet 825'

Abandoned Oil Well Gas Well _____ Input Well _____ SWD Well _____ D&A _____

Other well as hereinafter indicated _____

Plugging Contractor H & H Casing Pulling Co. License Number 6053

Address 1427, N. Halsted, Hutchinson, Ks. 67501

Company to plug at: Hour: 10:00 AM Day: 3 Month: 1 Year: 1983

VERBAL PLUGGING ORDERS GIVEN TO Don Hurst

(company name) H & H Casing Pulling Co. (phone) 316-665-5111

were: Order 165 lbs. cement, 50 posmix - 4% sal. - 3% lal. ll., 5 lbs. hully,
15 lbs. bal. & 8 5/8" plug.

Signed Walt J. Schab
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 12:50 PM Day: 3 Month: 1 Year: 1983

ACTUAL PLUGGING REPORT 8 5/8" - 825' S.P. cas. w/ 400 lbs. cement. 4 1/2" set at 3545'
w/ 140 lbs. Top perf at 3482'. Plugged bottom, pumped 20 lbs 50 posmix
4% sal. - 3% lal. ll. followed w/ plug to 3300'. Slot pipe 2 times & recovered 2485'.
Pumped in 8 5/8" S.P., 4 hully, 12 lbs. sal., 65 lbs. cement, 3 lbs. sal., 1 lb.
hully, released plug & followed w/ 100 lbs. cement.

Maximum pressure 700 pounds

Remarks: _____

STATE RECEIVED
COMMISSION

JAN 10 1983

CONSERVATION DIVISION
Wichita, Kansas

I hereby certify that the above plugging instructions were given as herein stated
and that I (did / ~~did not~~) observe this plugging.

INVOICED

DATE 1-12-83

INV. NO. 2100-W

Signed Walt J. Schab
(TECHNICIAN)

FORM CP-2/3
Rev. 9-82