

1 070616

NOV 12 1988

API NUMBER 15-145-21,287-0000  
Irregular Section

STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION App.  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

SW SE SW, SEC. 19, T 23 S, R 15 W/E

330 feet from S section line  
App. 3680 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 4973

Lease Name Campbell Well # 1  
County Pawnee 13390

Operator: Vantage Petroleum, Inc.  
Name & Address P.O. Box 553  
Great Bend, KS 67530-0553

Well Total Depth 4120 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 552

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Emphasis Oil Operations License Number 8241

Address Box 819, Russell, KS 67665

Company to plug at: Hour: 5:30 a.m. Day: 12 Month: 11 Year: 19 88

Plugging proposal received from Bill Owens  
(company name) Emphasis Oil Operations (phone) 913-483-3518

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2045' KB  
1st plug at 1000' with 50 sx cement, 2nd plug at 550' with 40 sx cement, Anhydrite 977-1004'  
3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

DEC 2 1988

Plugging Proposal Received by Dan Goodrow  
Wichita, Kansas (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 8 a.m. Day: 12 Month: 11 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 1000' with 50 sx cement,  
2nd plug at 550' with 40 sx cement,  
3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement,  
Water well plugged with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.  
(If additional description is necessary, use BACK of this form.)

INVOICED observe this plugging.

Signed Dan Goodrow (TECHNICIAN)

DATE DEC 8 1988

INV. NO. 23213

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date: November 4, 1988

API Number 15-145-21,287-0000 IRREGULAR SECTION

OPERATOR: License # 04973 Name: Vantage Petroleum, Inc. Address: P.O. Box 553 City/State/Zip: Great Bend, KS 67530-0553 Contact Person: Tom Larson Phone: (316) 792-3664

APR SW SE SW Sec. 19 Twp. 23 S. Rg. 15 West 330 Ft. from South Line of Section APP. 3680 Ft. from East Line of Section (Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 08241 Name: Emphasis Oil Operations City/State: Russell, KS

Nearest lease or unit boundary line 330 feet County: Pawnee Lease Name: Campbell Well # 1 Ground surface elevation 2040 feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Depth to bottom of fresh water 240 Depth to bottom of usable water 240 Surface pipe by Alternate: 1 X 2 Surface pipe planned to be set 260 Conductor pipe required None Projected Total Depth 4100 feet Formation: Arbuckle

Well Drilled For: Oil Storage Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 11/1/88 Signature of Operator or Agent Thomas J. Owen Title: Sec/Treas

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 260 feet per Alt. This Authorization Expires 5-2-89 Approved By 11-2-88

EFFECTIVE DATE: 7-88

RECEIVED STATE CORPORATION COMMISSION DEC 2 1988

Move in 11-11-88 set 550' of 8 5/8"

SW SE SW Sec. 19 Twp. 23 S. Rg. 15 West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep Base of Anhydrite or formation with 50 SX feet of 60-40 ppx w/6% gel.
2nd plug @ ft. deep Base of Permian or formation with 80 SX feet of
3rd plug @ ft. deep Base of surface pipe or formation with 40 SX feet of
4th plug @ ft. deep 40' or formation with 10 SX feet of
5th plug @ ft. deep or formation with feet of
(2) Rathole to surface minus 5 feet 15 SX (b) Mousehole to surface minus 5 feet 10 SX

PUSHER Bill Owen TD 4/20 FORMATION Arbuckle SURFACE PIPE 8 5/8" @ 552 ANHYDRITE 1009' ELEVATION 2045 KB STARTING TIME & DATE 11-12-88 5:30 AM COMPLETION TIME & DATE 11-12-88 8:00 AM 1st PLUG @ 1000 FT. W/ 50 SX 2nd PLUG @ 550 FT. W/ 40 SX 3rd PLUG @ 40 FT. W/ 10 SX 4th PLUG @ FT. W/ SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ SX WATER WELL PLUGGED W/ 10 SX CEMENT COMPANY Halliburton TECHNICIAN D.G.

60/40 670