

15-009-15770-00-00

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. 18-36

LOCATION CMB-SE-SE

SEC. 14 TWP. 16 RGE. 12-W

Dry Hole \_\_\_\_\_ Abandoned Oil Well X Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 4 Lease Mary Weber "East"

Operator W.H. Co. of Refinery, Kansas Address 530 W.N. Bldg - W. White - Kans.

Field \_\_\_\_\_ County Marion

Total Depth 3409 Feet.

(Describe briefly the manner in which the well was plugged)

No Surface Pipe in Hole -  
3 1/2" casing set at 3300 ft - Cemented with 35 sacks cement.  
Plugged back to 3050 ft with shot - Mixed  
5 sacks of cement at 3050 ft - Shot off & pulled the  
3 1/2" casing - Mixed to 2500 ft - Set back bridge & 48 sacks  
of cement at 2500 ft through the tubing - Mixed  
to 2000 ft bridge & 30 sacks cement at the surface

Well Supply Co - Plugging Contractor  
Conservation Div.

AUG 28 1950

STATE CORPORATION  
COMMISSION

Charles W. Couch  
District Conservation Agent

**PLUGGING**  
FILE SEC. 14 T. 16 R. 12 W.  
BOOK PAGE 18 OF 36

Date 8-25-50