

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. 87-22

LOCATION CNE-NW-NW

SEC. 6 TWP. 21 RGE. 15W

Dry Hole \_\_\_\_\_ Abandoned Oil Well ✓ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 1 Lease GROSS

Operator Gulf oil Corp Address Bobble Tulsa 2 Okla

Field \_\_\_\_\_ County Pawnee

Total Depth 3860 Feet.

(Describe briefly the manner in which the well was plugged)

8 7/8" 989' Circulated With 485# Cement  
5 7/8" 3860' Cemented With 160# Cement Casing Reformation  
3801' to 3806' casing leaks squeezed at 1695-1697 with  
100# cement squeezed at 1058 with 200# cement.  
Pulled 1300' 5 7/8" filled with Mud to 250' set rock  
bridge run 90# cement Mud to 35' set rock  
bridge run 10# cement case.

Jack Schull Pulling costs (Mutt)

**PLUGGING**  
FILE SEC 6 T 21 R 15W  
BOOK PAGE 22 LINE 22

RECEIVED  
STATE CORPORATION COMMISSION  
APR 3 - 1953  
CONSERVATION DIVISION  
Wichita, Kansas

W. L. Rice  
District Conservation Agent  
Date 4-3-53

CD

4-6-53