

4-060600

10-26

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15-009-22,618-00-00

SE NE NE /4 SEC. 32, 16 S, 12 W
4290 feet from S section line
330 feet from E section line

Operator license# 5427Lease Jacobs well # 2Operator: D.R. Lauck Oil Co., Inc.County Barton

Address: 221 S. Broadway
Suite #400
Wichita, Kansas 67202

Well total depth 3342 feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 295 feet

108.61

Aband. oil well X, Gas well , Input well , SWD , D & A Plugging contractor: Co Tools License# Address: Company to plug at: Hour: 10:00A.M Day: 26 Month: October Year: 94Plugging proposal received from: Melvin UrbanCompany: D.R. Lauck Oil Co., Inc. Phone: 316-263-8267

Were: Order 300 sxs. 60/40 posmix 10% gel and hulls.
Prior squeeze at 1135' w/250 sxs. with standing 1100# pressure.

Plugging Proposal Received by: Herb Deines
Plugging operations attended by agent? All[X], Part[], None[]

Completed: Hour: 11:15A.M, Day: 26, Month: October, Year: 94

Actual plugging report: 8 5/8" to 295'. 5 1/2" to 3334'. Perforate
at 300' - 450' - 850'. Tied onto annulus and pumped 50 sxs. cement
with 50# hulls. Max. P.S.I. 900#. S.I.P. 600#. Tied onto production
casing and pumped 250 sxs. cement with 250# hulls. Max. P.S.I. 1000#.
S.I.P. 700#.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD X BAD Anhy. plug: YES X NO
Bottom plug(in place): YES , CALC X, NO Dakota plug: YES X, NO
Plugged through TUBING , CASING X. Elevation: GL

I did[X] / did not[] observe the plugging.

INVOICED

DATE 11-2-94INV. NO. 41562

(agent)

Form CP-2/3

RECEIVED
STATE CORPORATION COMMISSION
OCT 31 1994
CONSERVATION DIVISION
WICHITA, KANSAS