ISTATE OF KANSAS STATE CORPOBATION COMMISSION Give All Information Completely Make Required Affidavit Mail or Deliver Report to: Conservation Division

# \5-009-05042-00-06 WELL PLUGGING RECORD

### FORMATION PLUGGING RECORD

Strike out upper line when reporting plug-ging off formations.

00 Bitting Building Vichita, Kansas						e. 13. Æ)(W
NORTH .						
i l i						Well No2
	Date well com	pleted . $7$	/22/42	Diy Hole/		19
1 1						19
	Application for	or plugging approv	$_{\rm red}$ 7/2	2/42		19
	Plugging com	menced	7/2	2/42		19
1 1	Plugging com	pleted	7/2	2/42	.,,	19
	Reason for ab	andonment of we	ll or producin	g formation	Dry Hole	
	***************************************					
i l				-		19.,
Locate well correctly on above		44	•			re plugging was con
Section Plat ne of Conservation Agent who supe	mencea (			exander		
lucing formation						
v depth and thickness of all water,			DU		Total Depth of	
IL, GAS OR WATER RECORDS	_	.OZIG.			(	CASING RECORD
Formation	Content	From	To	Size		Pulled Out
Formation	Content	From	-	J	Put In	
				10-3/4"0		None
			1			
			l .			
			1		'	
		1	1	1		j
				1		
			Ι΄.	ĺ		
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the and the angle of the state of the stat	character of s om 3398 w/ hea	to 3671,	Bridged	hole w/
feet for each plug	t or other plugs we set. Le with hes at 367° fi	re used, state the and the angle of the state of the stat	character of s om 3398 w/ hea	to 3671,	Bridged	hole w/
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the and the angle of the state of the stat	character of s om 3398 w/ hea	to 3671,	Bridged	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the and the angle of the state of the stat	character of s om 3398 w/ hea	to 3671,	Bridged	hole w/
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the and the angle of the state of the stat	character of s om 3398 w/ hea	to 3671,	Bridged	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the and the angle of the state of the stat	character of s om 3398 w/ hea	to 3671,	Bridged	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the	character of s  om 3398  w/ hea  and fil	to 3671,	Bridged 15°, bri	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set. Le with hes at 367° fi	re used, state the	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set.  Le with hea at 367° finds cement or	re used, state the	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set.  Le with hea at 367° finds cement or	re used, state the avy mud frilled hole bridge	character of s  om 3398  w/ hea: and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set.  Le with hea at 367° finds cement or	re used, state the	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set.  Le with hea at 367° finds cement or	re used, state the	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/ dged hole
feet for each plug Filled hol 15 sacks cement	t or other plugs we set.  Le with hea at 367° finds cement or	re used, state the	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/dged hole
Filled hol 15 sacks cement and put lo sacks	tor other plugs we set.  Le with hes at 367° fis cement or	re used, state the avy mud frilled hole bridge	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/dged hole
Filled hol 15 sacks cement and put lo sacks	tor other plugs we set.  Le with hes at 367° fis cement or	re used, state the avy mud frilled hole bridge	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/dged hole
Filled hol  15 sacks cement and put lo sacks  Correspondence regarding this wel	tor other plugs we set.  Le with hes at 367° fis cement or	re used, state the avy mud frilled hole bridge	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to  led to su	Bridged 15°, bri	hole w/dged hole
Filled hol 15 sacks cement and put lo sacks	tor other plugs we set.  Le with hes at 367° fis cement or	re used, state the avy mud frilled hole bridge	character of s  om 3398  w/ hea  and fil	to 3671,  vy mud to led to su  this sheet)	Bridged 15°, bri	hole w/dged hole
Filled hold 15 sacks cement and put lo sacks  Correspondence regarding this well ress 614 Bitting	tor other plugs we set.  Le with hes at 367° fine to the set of th	re used, state the livy mud frilled hole bridge	om 3398 w/ hea and fil	to 3671, vy mud to led to su	Bridged 15°, bri	hole w/dged hole
Filled hold 15 sacks cement and put lo sacks  Correspondence regarding this well ress. 614 Bitting	tor other plugs we set.  Le with hea at 367' find the set of the s	re used, state the avy mud frilled hole bridge	character of s  om 3398  w/ hear  and fil  Texas (  ansas	to 3671,  yy mud to led to su	Bridged 15°, bri	hole w/ dged hole
Filled hold 15 sacks cement and put lo sacks  Correspondence regarding this well fress 614 Bitting TE OF KANSAS M. C. HARRELL	tor other plugs we set.  Le with heat 367' fis cement or cement or set.  (If additionall should be address Bldg W	re used, state the avy mud frilled hole bridge    July   J	om 3398 w/ hear and fil  y, use BACK of Texas ansas  DGWICK	to 3671,  yy mud to led to su  this sheet)  Company  , ss. ner) or (owner or	Bridged 15°, bri rface.	hole w/dged hole
Filled hol  15 sacks cement and put lo sacks  Correspondence regarding this well ress. 614 Bitting  TE OF KANSAS M. C. HARRELL g first duly sworn on cath, says: 7	tor other plugs we set.  Le with hes at 367° fis cement or seement	re used, state the avy mud frilled hole bridge  1 bridge  2 bridge  1 chita, K	om 3398 w/ hea: and fil Texas ansas  DGWICK aployee of ownstatements, an	to 3671,  yy mud to led to su  this sheet)  Company  , ss. ner) or (owner or	Bridged 15°, bri rface.	hole w/dged hole
Filled hol  15 sacks cement and put lo sacks  Correspondence regarding this well ress 614 Bitting  TE OF KANSAS M. C. HARRELL g first duly sworn on oath, says: 7	tor other plugs we set.  Le with hes at 367° fis cement or seement	description is necessared to The Vichita, K	om 3398 w/ hear and fil Texas ansas  DGWICK aployee of own statements, an	to 3671,  yy mud to led to su  this sheet)  Company  , ss. ner) or (owner or	Bridged 15°, bri rface.	hole w/dged hole
Correspondence regarding this well ress 614 Bitting  TE OF KANSAS  M. C. HARRELL  g first duly sworn on oath, says: 7	tor other plugs we set.  Le with hes at 367° fis cement or seement	description is necessared to The Vichita, K	om 3398 w/ hear and fil  y, use BACK of Texas ansas  DGWICK aployee of own statements, an	to 3671,  yy mud to led to su  this sheet)  Company  , ss.  ner) or (owner or and matters herein	Bridged 15°, bri rface.	hole w/dged hole
Correspondence regarding this well ress 614 Bitting  TE OF KANSAS  M. C. HARRELL  g first duly sworn on oath, says: 7	tor other plugs we set.  Le with hes at 367° fis cement or seement	description is necessared to The Vichita, K	om 3398 w/ hear and fil  y, use BACK of Texas ansas  DGWICK aployee of own statements, an	to 3671,  yy mud to led to su  this sheet)  Jompany  , ss. ner) or (owner sering and matters herein	Bridged 15°, bri rface.	hole w/dged hole
Filled hold 15 sacks cement and put lo sacks  Correspondence regarding this well ress 614 Bitting  TE OF. KANSAS  M. C. HARRELL  g first duly sworn on oath, says: Tribed well as filed and that the san	tor other plugs we set.  Le with heat 367' first I have knowled are true and correct to the set.	description is necessared to The Vichita, K.  TY OF SE (em edge of the facts, rect. So help me (Signature)	om 3398 w/ hear and fil  Texas ansas  DGWICK aployee of own statements, and God.	to 3671,  yy mud to led to su  this sheet)  Jompany  , ss. ner) or (owner sering and matters herein	Bridged 15°, bri rface.	hole w/dged hole  above-described well the log of the above
Filled hold 15 sacks cement and put lo sacks  Correspondence regarding this well ress 614 Bitting  TE OF. KANSAS  M. C. HARRELL  g first duly sworn on oath, says: Tribed well as filed and that the san	tor other plugs we set.  Le with heat 367' first I have knowled are true and correct to the set.	description is necessared to The Vichita, K.  TY OF SE (em edge of the facts, rect. So help me (Signature)	om 3398 w/ hear and fil Texas (ansas DGWICK aployee of own statements, an	to 3671,  yy mud to led to su  this sheet)  Company  , ss. ner) or (ox nex send matters herein	Bridged 15°, bri rface.	hole w/dged hole  above-described well the log of the above
Correspondence regarding this weldress 614 Bitting	tor other plugs we set.  Le with heat 367' first I have knowled are true and correct to the set.	description is necessared to The Vichita, K.  TY OF SE (em edge of the facts, rect. So help me (Signature)	om 3398 w/ hear and fil Texas (ansas DGWICK aployee of own statements, an	to 3671,  yy mud to led to su  this sheet)  Company  , ss. ner) or (ox nex send matters herein	Bridged 15°, bri rface.	hole w/dged hole  above-described well the log of the above
Filled hold sacks cement and put lo sacks  Correspondence regarding this weld dress 614 Bitting  ATE OF KANSAS  M. C. HARRELL  Ag first duly sworn on oath, says: To be well as filed and that the same of the sam	tor other plugs we set.  Le with heat 367' first I have knowled are true and correct to the set.	description is necessared to The Vichita, Konge of the facts, seeds of the facts, seed	om 3398 w/ hear and fil Texas (ansas DGWICK aployee of own statements, an	to 3671,  yy mud to led to su  this sheet)  Jompany  , ss. ner) or (owner sering and matters herein	Bridged 15°, bri rface.	hole w/dged hole  above-described well the log of the above

19-4174

6-42—6M

# LOG OF WELL

Form PO-214 Sheet 1 (1-40) 17M

	he Texas C	- Charles					_	•				24-44
	angas					outs	<u> </u>		_WELL NO		(Two)	
STATE AN	ansas			H	SHIT CO	<u>n</u>	TWP	<u> 16 a</u>	RANGE	13 %	SEC	4
LOCATION OF W	ell Couser	r NW S	· <del>T</del>			<u> </u>		· · · · · · · · · · · · · · · · · · ·				<u> </u>
COMMENCED RIG	GING UP 6/	30/42	сомм	ENCED DRIL	LING	7/3/4	2	COMPLE	TED DRILLI	NG 7	122/42	
DAY DRILLER											Payne	
CABLE FROM		_то		ROTAR	Y FROM	0_		то <u>33</u> 9	98 <u> </u>	_COMPANY RI	G NO	
TOTAL DEPTH	3398	MEA	SURED BY.	M	. C.	Harrel		ELEVAT		1924	<del>-</del>	<del></del>
				CAS	ING	REC	ORD					-
SIZE	WEIGHT -	PUT IN V	VELL INS.	PULLED FEET	OUT INS.	LOST IN V	VELL_	5HO LENGTH	MAKE	KIND	PACKERS LENGTH	SET A
-7/4 #OD	7.0. 2 2		-  -	1221	183.		183.	LENGIA	MAKE	KIND	LENGIA	- SEI A
-3/4"OD 3-Ga.S.W.		370			-	<del></del>					-	<del></del>
			- <del> </del>  -								 	
			_  -	<del></del> :	_				<u> </u>	_	\ <u> </u>	
					_							
······································					_	<u>.</u>			<u> </u>	- <u></u>		
					_							
	j											
	<del> </del>		-		-ii							
	NTED? W/ 125		w	HERE SET			AND INS.		PERF	ND INS. ORATED		
NER: STATE SIZE	E AND WEIGHT.		WI	HERE SET	FL	E	AND INS.		PERF	ORATED		
INER: STATE SIZE	E AND WEIGHT.		WI	HERE SET	MEN	FT. .ush-joint	AND INS.		PERF	ORATED	OUTFIT	
NER: STATE SIZE	E AND WEIGHT		WI	HERE SET	MEN	ER RODS	AND INS.		PERF	FED.		
INER: STATE SIZE	E AND WEIGHT.	COUP	LING	HERE SET	M E N	ER RODS	COR		PERF	PUMPING		
INER: STATE SIZE	E AND WEIGHT.	COUP	LING	HERE SET	M E N	ER RODS	COR		PERF	PUMPING		
NER: STATE SIZE	E AND WEIGHT.	COUP	LING	HERE SET	M E N	ER RODS	COR		PERF	PUMPING		
INER: STATE SIZE  OW PUT TOGETHI  EMARKS:  SIZE	E AND WEIGHT.	FEET	LING	HERE SET	MEN SUCK	USH-JOINT  TRE  ER RODS  SIZE A	COR		PERF(	PUMPING		
NER: STATE SIZE  OW PUT TOGETHI  EMARKS:  SIZE  FLOWING, PUMPI	TUBING WEIGHT	Pry Dry	LING	E Q U I F	MEN SUCK INS.	USH-JOINT	C O R	D	PERFO	PUMPING DESCRIPTION, KI	ND, SIZE, ETC,	
NER: STATE SIZE  OW PUT TOGETHI  EMARKS:  SIZE  FLOWING, PUMPI	TUBING WEIGHT WEIGHT ING, GASSER OR DRY_	COUP	LINGE	E Q U I F  FEET  PRODUCTION SHUT	MEN SUCK INS.	T RE ER RODS SIZE A	COR	D	PERFO	PUMPING DESCRIPTION, KI	ND, SIZE, ETC,	
SIZE  FLOWING, PUMPI  IF GAS WELL, OP	TUBING WEIGHT WEIGHT ING, GASSER OR DRY_	-coup	LING	FEET PRODUCTION	MEN SUCK INS.	T RE ER RODS SIZE A	COR	D	PERFO	PUMPING DESCRIPTION, KI	ND, SIZE, ETC.	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT	TUBING WEIGHT  ING, GASSER OR DRY PEN FLOW CAPACITY	Pry Coup	INS.	FEET PRODUCTION SHUT	PMEN SUCK INS.	T RE ER RODS SIZE A	C O R	DP	PERFO	PUMPING DESCRIPTION, KI	ND, SIZE, ETC.	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT NUMBER OF SHEL	TUBING WEIGHT  ING, GASSER OR DRY_ PEN FLOW CAPACITY_	Dry  EET.	INS.	PRODUCTION SHUT	MEN SUCK INS.	T RE ER RODS SIZE A SHOURS OF SHOT, Q	C O R	DPI	PERFO	PUMPING DESCRIPTION, KI	ND, SIZE, ETC.	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT NUMBER OF SHEL BOTTOM OF SHOT	TUBING WEIGHT  ING, GASSER OR DRY_ PEN FLOW CAPACITY	-COUP	LING	PRODUCTION SHUT OF SHELLS	PMEN SUCK INS.	T RE ER RODS SIZE A SHOURS OF SHOT, Q	COR	DPI	PERFO	PUMPING DESCRIPTION, KI	ND, SIZE, ETC.	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT NUMBER OF SHEL BOTTOM OF SHOT	TUBING WEIGHT  ING, GASSER OR DRY_ PEN FLOW CAPACITY  / LLS  LS  TUBING	COUP FRET	INS.  SIZE  IN  AI  NUMBER O	PRODUCTION SHUT OF SHELLS NCHOR	MEN SUCK INS.	T RE ER RODS SIZE A	COR	DPI	PERFO	PUMPING DESCRIPTION, KI	ND, SIZE, ETC.	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT NUMBER OF SHEL BOTTOM OF SHOT TOTAL DEPTH OF	TUBING WEIGHT  ING, GASSER OR DRY PEN FLOW CAPACITY  LLS LS F WELL TER SHOT	L'LY  FEET	SIZE O	PRODUCTION SHUT OF SHELLS ICHES NCHOR F SHOT BLS, PER DA	PMEN SUCK INS. I FIRST 24 IN PRESS SIZE	USH-JOINT  TRE  ER RODS  SIZE A  SHOURS  OF SHOT, Q	COR	DPI	PERFO	PUMPING DESCRIPTION, KI	BBLS	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT NUMBER OF SHE BOTTOM OF SHOT TOTAL DEPTH OF PRODUCTION AFT	TUBING WEIGHT  ING, GASSER OR DRY PEN FLOW CAPACITY  LLS LS F WELL TER SHOT	Dry FEET.	LINGSIZE (	PRODUCTION SHUT OF SHELLS ICHES NCHOR F SHOT BLS, PER DA	MEN SUCK INS. I FIRST 24 IN PRESS SIZE IN SIZE IN SIZE	USH-JOINT  TRE  ER RODS  SIZE A  SHOURS  OF SHOT, Q	COR	DPI	PERFO	PUMPING DESCRIPTION, KI	BBLS	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT NUMBER OF SHE BOTTOM OF SHOT TOTAL DEPTH OF PRODUCTION AFT	TUBING  WEIGHT  ING, GASSER OR DRY_ PEN FLOW CAPACITY_  /  LLS  WELL_ FER SHOT  ER LLING DEEPER	Dry FEET.	SIZE IN NUMBER OF	PRODUCTION SHUT OF SHELLS ICHES NCHOR F SHOT SHOT COMPL	MEN SUCK INS. I FIRST 24 IN PRESS SIZE IN PRESS	USH-JOINT  TRE  ER RODS  SIZE A  SHOURS  SURE  OF SHOT, Q	COR	D  INCHES,  TOP OF  WELL BR ON BEFORE SH  BY  DRILL	PERFO	PUMPING DESCRIPTION, KI	BBLS	
FLOWING, PUMPI IF GAS WELL, OP KIND OF SHOT NUMBER OF SHE BOTTOM OF SHOT TOTAL DEPTH OF PRODUCTION AFT NAME OF SHOOT COMMENCED DRI	TUBING  WEIGHT  ING, GASSER OR DRY_ PEN FLOW CAPACITY_  /  LLS  WELL_ FER SHOT  ER LLING DEEPER		SIZE ON MUMBER OF BEST	PRODUCTION SHUT OF SHELLS NCHOR F SHOT COMPL TIRST 24 HO	MEN SUCK INS.	USH-JOINT  TRE  ER RODS  SIZE A  SHOURS  SURE  OF SHOT, Q	COR	D  INCHES,  TOP OF  WELL BR ON BEFORE SH  BY  DRILL	PERFO	PUMPING DESCRIPTION, KI	BBLS	
FLOWING, PUMPI IF GAS WELL, OF KIND OF SHOT NUMBER OF SHE BOTTOM OF SHOT TOTAL DEPTH OF PRODUCTION AFT NAME OF SHOOT COMMENCED DRI	TUBING WEIGHT  ING, GASSER OR DRY_ PEN FLOW CAPACITY_  LLS  WELL_ TER SHOT  ELLING DEEPER		SIZE ON MUMBER OF BEST	PRODUCTION SHUT OF SHELLS NCHOR F SHOT COMPL TIRST 24 HO	MEN SUCK INS. I FIRST 24 IN PRESS SIZE IN PRESS	USH-JOINT  TRE  ER RODS  SIZE A  SHOURS  SURE  OF SHOT, Q	COR	D  INCHES,  TOP OF  WELL BR ON BEFORE SH  BY  DRILL	PERFO	PUMPING DESCRIPTION, KI	BBLS	

.....

Form PO-214 Sheet 2 (7-49) 20M

## LOG OF WELL

SHEET NO.\_2\_

District KANSAS  PORMATION	Owne	er Tries	COLOR	HARD OR SOFT	DEPTH CORES	remarks
<del></del>				- 5% ave 1	TAKEN	
urface Clay lue Shale	60 170	60	l ,			*
lue Shale	170 185	110	<b>!</b>	1		
luo Shalo	230	ريد 24	l ,			
stor Sand	240	15 10 35 50	1 ,	1		
iter Sand	275	35	White			
d Rock	275 325 329 357 367	56	1	1		
me	329	28	Į.			
d Rock	<b>35</b> <u>7</u>	58	\$15 PF :			
nele sola & Sand	507	10	Blue			
wie & Sand :	591 840	224	Į.			
sio e kod Rod	915	75	1	1		
hwant to	948	249 75 33 612	ĺ			
ale	1550	612	(	1		
me & Shelo	1670	1110	(	1		
.20	1700	30	1			
ne & Shale	2073	30 373 12	t	1		
MO okon Ismo	2085	12	{			
oken Line	5150	35 40 28	1			
ne & Shale No	2160 2188	40	ļ			
no ale & Lime	5528 5109	KO	[			•
re To or time	2250	50 12	•	1		
ale	2250 2255	Îĥ			1	
<b>70</b> 074	2280	15 15 215 111			1	
me & Shale	2495	215		į į	1	
ile "	2495 2605	1111			1	
5.0	2658 2670	52 12	-		1	
Me .	2670	13		Hard	1	
	2676	6		Med.	1	
MO ma & Shela	2686	10 88		Hard	1	
me & Shale	2774 2768	88		}	1	
M.0 £10	5206	14 18		Hard	1.	
elo Be	2824	18		Soft	I	Top Anhydrite 896
ing Ng	2845	21		Med Hd.	I	Top Lansing 3142
mu Mo	3023	178			•	Porosity 3155-58
ne .	<b>3064</b> .			Hará	<del>(</del>	3170-70, 3222-30
er e	3078	14		Broken	I	Top Arbuckle 3382
100	3110	32			1	
me & Shele	3160	50		-	Į.	Cores:
NO No. A. Shola	3170 2018	10		Hard	Į.	3384-87 - 3' Recove
se & Shele	3218	40		Man #	l	6"Arb, Dol, -Irr, Red
no Bo	3222 3238	41 14 32 50 10 48 16 66		Hard Soft	Ţ	6"Chert- Pink & Whi
80 80	7304	KK.		Hard	1	6"Dol. Broken w/ sha
190 NG	3304 3328 3382			Add A Ca	l	1º Dol Greenish
to & Shale	3382	52		1	1	6" Dol xatho Porc
ackle Lime	358 <b>ā</b>	24 54 2 3		1	Į.	3387-92 - 5' Recove
l Chert & Lime	3384 3387	3		1	Į.	5° dol. xzt.Solid.0
i.e	3398	lī		1	1	3392-98 - 1-1/2' Re
		1		i	1	xst, Dol. Sandy in
Cotal Depth	3398				Ļ	bottom-Sulphur) write
) & # 7/0×/+0				1	[,	odor
0 & A 7/23/42		[	1_4" " "	1	(بار)	AUE 2-1921-180
		1 1		43 20	1	NIE 2 - 1921-18
		1 4.	ρ <mark>ίμ</mark> α. Ευναγού Εν	43 . 21	ψ.	ALL TO
		] /2	200% - No	-   -		The state of the s
		1				15/
						1 1 20 20
				(		
				1		
,					1	