

1052304

TO: STATE CORPORATION COMMISSION 1-19

API NUMBER 15-185-21,062-0000  
NE NW NE SEC. 21, T 21 S, R 13 W

CONSERVATION DIVISION - PLUGGING SECTION 4950 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 1650 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202 LEASE NAME HOFFMAN A WELL # 6

TECHNICIAN'S PLUGGING REPORT COUNTY STAFFORD 120.41

OPERATOR LICENSE # 31925 WELL TOTAL DEPTH 3705 FEET

OPERATOR: QUALITY WELL SERVICE PRODUCTION CSG: SIZE 5 1/2" @ 3704' WITH 175 SX

NAME AND 249 BETH DRIVE SURFACE CASING: SIZE 8 5/8" @ 357' WITH 300 SX

ADDRESS STERLING, KS 67579

ABANDONED OIL WELL X GAS WELL INPUT WELL SWD WELL D/A

OTHER WELL AS HEREINAFTER INDICATED

PLUGGING CONTRACTOR QUALITY WELL SERVICE LICENSE NUMBER 31925

ADDRESS SAME AS ABOVE

COMPANY TO PLUG AT: HOUR: 12:00 PM DAY: 19 MONTH: 01 YEAR: 1999

PLUGGING PROPOSAL RECEIVED FROM RICHARD MCINTIRE

(COMPANY NAME) QUALITY WELL SERVICE (PHONE) 316-727-3410

WERE: PERFS AT 3367-3395

1ST PLUG SANDED TO 3301'.

2ND PLUG AT 750' WITH 10 SX GEL & 50 SX CEMENT.

3RD PLUG AT 390' WITH 50 SX CEMENT.

4TH PLUG AT 40' WITH 10 SX CEMENT.

PLUGGING PROPOSAL RECEIVED BY RICHARD LACEY

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL X PART NONE

OPERATIONS COMPLETED: HOUR: 3:00 PM DAY: 19 MONTH: 01 YEAR: 1999

ACTUAL PLUGGING REPORT

1ST PLUG SANDED TO 3301'. 1-25-99

2ND PLUG AT 750' WITH 10 SX GEL & 50 SX CEMENT.

3RD PLUG AT 390' WITH 50 SX CEMENT.

4TH PLUG AT 40' WITH 10 SX CEMENT.

REMARKS: USED 60/40 POZMIX 6% GEL BY UNITED. RECOVERED 2644' OF 5 1/2" CASING.  
(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I (DID) OBSERVE THIS PLUGGING.

SIGNED Richard W. Lacey (TECHNICIAN) FORM CP-2/3



1-26-99  
60581 1-19