

3-14-88

To: 1 040066
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 097-20,614-0000
NW NW NW, SEC. 11, T 28 S, R 16 WEX
4950 feet from S section line
4950 feet from E section line

TECHNICIAN'S PLUGGING REPORT
Operator License # 4548
Operator: ONEOK Exploration
Name & Address: RR 1, Box 122A
El Reno, OK 73036-9702

Lease Name Rinkel A Well # 2-11
County Kiowa 153.99
Well Total Depth 4738 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 368

Abandoned Oil Well Gas Well Input Well _____ SWD Well _____ D&A _____
Other well as hereinafter indicated _____

Plugging Contractor Clarke Corporation License Number 5105
Address P.O. Box 187, Medicine Lodge, KS 67104

Company to plug at: Hour: 10 a.m. Day: 14 Month: 3 Year: 19 88

Plugging proposal received from Elmo Morgenstern
(company name) Clarke Corporation (phone) 316-886-5665

were: 5 1/2" at 4737' PBD 4708' Perfs at 4683-88'
1st plug sand back to 4633' and dump 5 sx cement on top of sand through bailer,
2nd plug pump 4 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8" wiper plug and pump 120 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____
Operations Completed: Hour: 10:45 a.m. Day: 14 Month: 3 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug sanded back to 4633' and dumped 5 sx cement on top of sand through bailer,
2nd plug pumped down 8 5/8" with 400 lbs. hulls, 10 sx gel, 50 sx cement, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 120 sx cement.

Maximum pressure 600 psi and shut in 50 psi.

Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2650' of 5 1/2" casing.
(if additional description is necessary, use BACK of this form.)

MAR 23 1988
3-23-88

CONSERVATION DIVISION
STATE CORPORATION COMMISSION
WICHITA, KANSAS

INVOICED
observe this plugging.

DATE 3-25-88
NW. NO. 20206

Signed Stephen J. Pfeiffer (TECHNICIAN)