

To: 1 051547 4-17  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 185-22,832-0000 259  
100' N of  
SW SW SE, SEC. 7, T. 21 S, R. 11 W/EX  
430 feet from S section line  
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5056

Lease Name Schlochtermeyer Well # 2-7

Operator: F.G. Holl Company

County Stafford

Name & Address P.O. Box 780167

Well Total Depth 3575 116.18 feet

Wichita, KS 67278-0167

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 262

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sterling Drilling Company License Number 5142

Address P.O. Box 129, Sterling, KS 67579

Company to plug at: Hour: 5 a.m. Day: 17 Month: 4 Year: 19 92

Plugging proposal received from Vaughn Thompson

(company name) Sterling Drilling Company (phone) 316-278-2131

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 439'

1st plug at 600' with 50 sx cement,

2nd plug at 290' with 40 sx cement,

3rd plug at 60' with 15 sx cement,

4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Richard Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 7 a.m. Day: 17 Month: 4 Year: 19 92

ACTUAL PLUGGING REPORT 1st plug at 600' with 50 sx cement,

2nd plug at 300' with 40 sx cement,

3rd plug at 60' with 15 sx cement,

4th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by HOWCO.

If additional description is necessary, use BACK of this form.  
I (and / or did not) observe this plugging.

**INVOICED**

DATE 5-14-92

WV. NO. 35244

Signed Richard W. Lacey  
(TECHNICIAN)

STATE CORPORATION COMMISSION  
RECEIVED  
MAY 1 1992  
CONSERVATION DIVISION  
Wichita, Kansas

EFFECTIVE DATE: 4-13-92

FORM MUST BE TYPED

DISTRICT # 1

State of Kansas NOTICE OF INTENTION TO DRILL 15-185-22,832-0000

FORM MUST BE SIGNED

SEAL Yes No

Must be approved by the K.C.C. five (5) days prior to commencing well

ALL BLANKS MUST BE FILLED

Expected Spud Date April 13, 1992 100' Spot N of SW SW SE Sec 7 Twp 21 S, Rg 11W East West

OPERATOR: License # 5056 Name: P. G. Holl Company Address: P.O. Box 780167 City/State/Zip: Wichita, Kas., 67278-0167 Contact Person: Elwyn H. Nagel Phone: (316) 684-8481

430' FSL feet from South North line of Section 2310' FEL feet from East West line of Section IS SECTION X REGULAR IRREGULAR?

CONTRACTOR: License # 5142 316-278-2121 Name: Sterling Drilling Company P.O. Box 4129 Sterling 67579 Well Drilled For: Well Class: Type Equipment:

(NOTE: Locate well on the Section Plat on Reverse Side) County: Stafford Lease Name: SCHLOCHTERMEIER Well # 2-7 Field Name: Sandago

X Oil ... Enh Rec X Infield X Mud Rotary X Gas ... Storage ... Pool Ext. ... Air Rotary ... OWD ... Disposal ... Wildcat ... Cable ... Solenoid ... # of Holes ... Other

Is this a Prorated/Spaced Field? ... yes X no Target Formation(s): Arbuckle Simp. Sd. LKC Nearest lease or unit boundary: 330' Ground Surface Elevation: Est. 1800' feet MSL

If OWD, old well information as follows: Operator: Well Name: Comp. Date: Old Total Depth:

Water well within one-quarter mile: ... yes X no Public water supply well within one mile: ... yes X no Depth to bottom of fresh water: 140' Depth to bottom of usable water: 220' Surface Pipe by Alternate: X 1 2 Length of Surface Pipe Planned to be set: 240'

Directional, Deviated or Horizontal wellbore? ... yes X no If yes, true vertical depth: Bottom Hole Location:

Length of Conductor pipe required: NA Projected Total Depth: 3625' Formation at Total Depth: Arbuckle Water Source for Drilling Operations:

Exp. 10/8/92

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

DWR Permit # (Applied for by Sterling Drig.) Will Cores Be Taken? ... yes X no If yes, proposed zone: 240' Alt. I Req.

Pusher Van Thompson INIT. Sum LENGTH SURFACE PLANNED 240 RESERVE PIT STATUS- REMOVE FLUID LINED after salt sect. bbls. when done bbls. RATHOLED AHEAD? Y N SIZE HOLE SURFACE PIPE 8 3/4 @ 260 CONDUCTOR ANHYDRITE T- 479 B- ELEVATION TD 3575 FORMATION RAN PIPE @ DV TOOL ALT II DONE SX Y N Arbuckle Plug @ 507 Ft. W/ 50 SX Hug./Council @ Ft. W/ SX Anhydrite Base @ Ft. W/ SX 1/2 Base Anyh. @ 600 Ft. W/ 50 SX 1/2, 1/2 Plug @ 300 Ft. W/ SX Bottom Surface @ 290 Ft. W/ 40 SX 40' Plug @ 40 Ft. W/ 15 SX RAT HOLE CIRC/W 19 SX MOUSE HOLE W/ SX WATER WELL SX (Irr. Well Pond Hauling) TECHNICIAN L. L DATE 4-16-92 STATE CORP. COMMISSION RECEIVED 1992 MAY 17 11:27 (AM/PM) DATE 4-17-92 CEMENT WORK