

3-5  
API NUMBER 15- 097-21,268-0000 97R

To: 1031185  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

C N/2 N/2, SEC. 13, T 28 S, R 17 W/E  
4800 feet from S section line  
2570 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 6725

Lease Name Bevans Well # 1  
County Kiowa 157.62

Operator: Eric Waddell Company  
Name & Address P.O. Box 349  
Natoma, KS 67651-0349

Well Total Depth 4850 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 325.68

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Zigler Well Service Inc. License Number 30061

Address P.O. Box 873, Russell, KS 67665

Company to plug at: Hour: 1:30 p.m. Day: 5 Month: 3 Year: 19 92

Plugging proposal received from Eric Waddell

(company name) Eric Waddell Co. (phone) 913-885-4497

were: 4 1/2" at 4849' w/150 sx cement, PBSD 4849', Perfs at 4746-49, 4752-55'

1st plug pump 150 sx cement down annulus,

2nd plug pump 250 sx cement down 4 1/2".

Plugging Proposal Received by Dan Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 3:45 p.m. Day: 5 Month: 3 Year: 19 92

ACTUAL PLUGGING REPORT Pumped 150 sx cement down annulus. Maximum pressure 200 psi and shut in 50 psi.

Pumped 210 sx cement down 4 1/2", filled casing, squeezed with 40 sx cement for a total of 250 sx cement in 4 1/2".

RECEIVED  
MAR 16 1992

Remarks: Used 60/40 Pozmix by Allied. No casing recovery.

3-16-92

(If additional description is necessary, use BACK of this form.)

I (did / did not) observe this plugging.

DATE 4-8-92

Signed Steve Stewart  
(TECHNICIAN)

INV. NO. 34 905

3-5 MAY 19 1992