KANSAS

Form CP-3 Rev. 6-4-68

STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

J. Lewis Brock
Administrator
245 North Water
Wichita. KS 67202

	API Number 15 - 185 21,110 (of this well)
	ris.
Complete Address Box 324, Gre	eat Bend, Ks. 56530
Lease Name Herb	Well No. 1
	Sec. 15 Twp. 21s Rge. 13 (E) (W) X
CountyStafford	Total Depth 3650
Abandoned Oil Well Gas	Well Input Well SWD Well D & A X
	ted
	Co., Tools.
"	License No.
•	:30 Am. Day 2 Month 10 Year 1980
The above well was plugged as	follows:
300' 8 5/8" casing w/280) sax cement. Set 50 sax cement plug at 600'-
300' 8 5/8" casing w/280 Set 40 sax cement plug a	sax cement. Set 50 sax cement plug at 600'-
300' 8 5/8" casing w/280 Set 40 sax cement plug a) sax cement. Set 50 sax cement plug at 600'-
300' 8 5/8" casing w/280 Set 40 sax cement plug a	sax cement. Set 50 sax cement plug at 600'-
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat	sax cement. Set 50 sax cement plug at 600'-
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat	sax cement. Set 50 sax cement plug at 600'-
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat	sax cement. Set 50 sax cement plug at 600'-
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat	sax cement. Set 50 sax cement plug at 600'- at 300'-Bridge at 40' & 10 sax cement to 5' hole. Cemented by Howco.
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat '	sax cement. Set 50 sax cement plug at 600'- at 300'-Bridge at 40' & 10 sax cement to 5' hole. Cemented by Howco.
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat '	sax cement. Set 50 sax cement plug at 600'- at 300'-Bridge at 40' & 10 sax cement to 5' hole. Cemented by Howco. STATE CORPORATION O
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat ' ' I hereby certify that the abov	sax cement. Set 50 sax cement plug at 600'- at 300'-Bridge at 40' & 10 sax cement to 5' hole. Cemented by Howco. STATE CORPORATION O
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat ' I hereby certify that the abov	sax cement. Set 50 sax cement plug at 600'- at 300'-Bridge at 40' & 10 sax cement to 5' hole. Cemented by Howco. The well was plugged as herein stated. Signed: Well Plugging Supervisor
300' 8 5/8" casing w/280 Set 40 sax cement plug a below Gl. 10 sax in rat ' ' I hereby certify that the abov	sax cement. Set 50 sax cement plug at 600'- at 300'-Bridge at 40' & 10 sax cement to 5! hole. Cemented by Howco. STATE CORPORATION O