

To: 1052031
STATE CORPORATION COMMISSION
Wichita State Office Bldg. PLUGGING SECTION
130 S. Market, Room 2078
Wichita, KS 67202

API NUMBER 15- 093-21,501-0000 191R
SW NW, SEC. 7, T. 21 S, R. 35 W
1980 feet from NE section line
660 feet from WE section line

TECHNICIAN'S PLUGGING REPORT
Operator License # 5422
Operator: Abercrombie Drilling, Inc.
Name:
Address 150 N. Main, Ste. 801
Wichita, KS 67202

Lease Name Houloose Well # 1
County Kearny 166.56
Well Total Depth 5125 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 307.81

Abandoned Oil Well Gas Well Input Well SHD Well D&A X
Other well as hereinafter indicated

Plugging Contractor Abercrombie RTD, Inc. License Number 30684
Address 150 N. Main, Ste. 801, Wichita, KS 67202

Company to plug at: Hour: Day: 31 Month: 3 Year: 19 96

Plugging proposal received from Walter Brown
(company name) Abercrombie RTD, Inc. (phone) 316-262-1841

work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2251-63'
1st plug at Anhydrite base with 100 sx cement,
2nd plug at 2260' with 50 sx cement, 3rd plug at 1060' with 80 sx cement,
4th plug at 340' with 50 sx cement, 5th plug at 40' with 10 sx cement,
6th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Richard Lacey
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: Day: 31 Month: 3 Year: 19 96

ACTUAL PLUGGING REPORT 1st plug at 3010' with 100 sx cement,
2nd plug at 2260' with 50 sx cement,
3rd plug at 1060' with 80 sx cement,
4th plug at 340' with 50 sx cement,
5th plug at 40' with 10 sx cement,
6th plug to circulate rathole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION
APR 4 1996
4-4-1996

Remarks: Used 60/40 Pozmix 6% gel 1/4# Floseal by Allied.
(If additional description is necessary, use BACK of this form.)

INVOICED
Observe this plugging.

DATE 4-10-96

Signed Steve Shumant
(TECHNICIAN)

INV. NO. 45169

3-31

FOR KCC USE:

15.093.21501.0000

FORM C-1 7/91

EFFECTIVE DATE: 2-28-96

State of Kansas

FORM MUST BE TYPED

DISTRICT # 1

NOTICE OF INTENTION TO DRILL 093-21,501

FORM MUST BE SIGNED

SGA? Yes No

Must be approved by the K.C.C. five (5) days prior to commencing well.

ALL BLANKS MUST BE FILLED

Expected Spud Date 3 month day year 1996 FEB 23 P 12: 21 1980 Spot SW NW Sec 7 Twp 21 S, Rg 35 XX East West

OPERATOR: License # 5422 Name: Abercrombie Drilling, Inc. Address: 150 N. Main, Suite 801 Wichita, Ks. 67202 Contact Person: Mark R. Galyon Phone: (316)262-1841

660 feet from South North line of Section 660 feet from East West line of Section IS SECTION XX REGULAR IRREGULAR?

(NOTE: Locate well on the Section Plat on Reverse Side) County: Kearny

Lease Name: HOULOOSE Well #: 1 Field Name: WC

Is this a Prorated/Spaced Field? yes XX no Target Formation(s): LKC/Marmaton

Nearest lease or unit boundary: 660 Ground Surface Elevation: unknown EST. 3170 feet MSL

Water well within one-quarter mile: yes XX no Public water supply well within one mile: yes XX no

Depth to bottom of fresh water: 180 Depth to bottom of usable water: 1040

Surface Pipe by Alternate: 1 XX 2 Length of Surface Pipe Planned to be set: 260

Length of Conductor pipe required: -0- Projected Total Depth: 5150

Formation at Total Depth: Mississippi

Water Source for Drilling Operations: well farm pond XX other

CONTRACTOR: License #: 30684 Name: Abercrombie RTD, Inc.

Well Drilled For: Well Class: Type Equipment:

XX Oil Enh Rec Infield XX Mud Rotary Gas Storage Pool Ext. Air Rotary OWO Disposal XX Wildcat Cable Seismic; # of Holes Other

If OWO: old well information as follows: Operator: Well Name: Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes XX no If yes, true vertical depth:

Will Cores Be Taken? yes XX no If yes, proposed zone:

Bottom Hole Location: Exp. 8/23/96

200' Alt. II Req.

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq. It is agreed that the following minimum requirements will be met:

RECEIVED STATE CORPORATION COMMISSION APR 4 1996

Pusher: Walter Swann SPUD DATE: 3-20-96 INIT. n.l. LENGTH SURFACE PLANNED: 260-290' RESERVE PIT STATUS- REMOVE FLUID LINED after salt sect. bbls. when done bbls. RATHOLED AHEAD? Y N SIZE HOLE SURFACE PIPE 8 3/8 @ 30 7/8 CONDUCTOR ANHYDRITE T- 2251 B- 2263 ELEVATION RTD 5 25 FORMATION IRAN PIPE @ DV TOOL ALT II DONE SX Y N Arbuckle Plug @ Ft. W/ SX Hug./Council @ Ft. W/ SX Anhydrite Base @ 3010 Ft. W/ 100 SX 1/2 Base Anyh. @ 2260 Ft. W/ 50 SX 1/2, 1/2 Plug @ 1060 Ft. W/ 80 SX Bottom Surface @ 340 Ft. W/ 50 SX 40' Plug @ 40 Ft. W/ 10 SX RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ NO SX WATER WELL SX (Irr. Well Pond Hauling X) TECHNICIAN R. L DATE 3 TYPE OF CEMENT 60/40 y12 6% gel 1/4 F10 STARTING TIME (AM/PM) DATE 3/31/96 COMPLETION TIME (AM/PM) DATE 3/31/96 CEMENT COMPANY All Lead