

1052286

15-185-90186-0000

TO: STATE CORPORATION COMMISSION

8-27

API NUMBER 15-185-21,424-0000
SW SE SE SEC. 4, T 21 S, R 13 W

CONSERVATION DIVISION - PLUGGING SECTION 75 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 990 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202 LEASE NAME WILLCUT WELL # 1-3

TECHNICIAN'S PLUGGING REPORT COUNTY STAFFORD 11375

OPERATOR LICENSE # 32081 WELL TOTAL DEPTH 3500 FEET

OPERATOR: SMOKEY VALLEY RESOURCES, INC PRODUCTION CSG: SIZE 4 1/2 " FEET 3500'

NAME AND 1325 HWY 56 SURFACE CASING: SIZE 8 5/8" FEET 260'

ADDRESS LYONS, KS 67554

ABANDONED OIL WELL GAS WELL INPUT WELL SWD WELL E-8784 D/A

OTHER WELL AS HEREINAFTER INDICATED

PLUGGING CONTRACTOR MIKE'S TESTING & SALVAGE, INC LICENSE NUMBER 31529

ADDRESS PO BOX 467, CHASE, KS 67524

COMPANY TO PLUG AT: HOUR: 11:30 AM DAY: 27 MONTH: 08 YEAR: 1998

PLUGGING PROPOSAL RECEIVED FROM MIKE KELSO

(COMPANY NAME) MIKE'S TESTING & SALVAGE (PHONE) 316-938-2943

WERE:

1ST PLUG PUMP DOWN 4 1/2" WITH 200# HULLS & 210 SX CEMENT. MAXIMUM PRESSURE 1200#, SHUT-IN PRESSURE 600#. 2ND PLUG PRESSURED 8 5/8 X 4 1/2 ANNULAS WITH CEMENT TO 1000#.

PLUGGING PROPOSAL RECEIVED BY RICHARD LACEY

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL X PART NONE

OPERATIONS COMPLETED: HOUR: 1:30 PM DAY: 27 MONTH: 08 YEAR: 1998

ACTUAL PLUGGING REPORT

1ST PLUG PUMPED DOWN 4 1/2" WITH 200# HULLS & 210 SX CEMENT. MAXIMUM PRESSURE 1200#, SHUT-IN PRESSURE 600#. 2ND PLUG PRESSURED 8 5/8 X 4 1/2 ANNULAS WITH CEMENT TO 1000#.

REMARKS: 60/40 POZMIX 6% GEL BY ALLIED. NO CASING RECOVERED.

MARKER DEPTH: SQUEEZED AT 650' WITH 250 SX CEMENT.

(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I (DID) OBSERVE THIS PLUGGING.

DATE 9-2-98

SIGNED Richard W. Lacey (TECHNICIAN)

FORM CP-2/3

NV. NO. 51258

8-27

JAN 29 1999

RECEIVED
AS COPIED
SEP 0 1998