1120023 To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 TECHNICIAN'S PLUGGING REPORT		9-28-87 5.185.01676.000 API NUMBER 15- NA SW SW NE, SEC. 4, 'T 21 S, R 13 W/K 2970 feet from S section line 2310 feet from E section line	
Operator	License # 5238	Lease Name Schaffer	₩eII # 3-1
∆eme.	Petroleum Inc.	County Stafford	117.91
	Box 1447	Well Total Depth	3628 feet
	Great Bend, KS 67530	Conductor Pipe: Size_	feét
		Surface Casing: Size	3 5/8 feet 147
Abandoned	Oll Well Gas Well	Input WellXSWD	WellD&A
Other wel	t as hereinafter indicated		
Plugging Contractor Rockhold Engineering License Number 5111			
Address_Bo	ox 698, Great Bend, KS 67530		
· Comp any t e	o plug at: Hour: 2:30 p.m. Day:		Year:1987
	proposal received from Deacon Pr		<u> </u>
(company (name) Rockhold Engineering		(phone) 316-792-2506
	2" at 3628' PBTD 3538' Perfs at		
lst plug s	sand back to 3465' and dump 5 sx	cement on top of sand thro	ough bailer,
2nd plug p	pumped 3 sx hulls, 10 sx gel,50 s	x cement, 10 sx gel, 1 sx	hulls, release 8 5/8"
wiper plug	g and pump 125 sx cement.		
	Plugging Prop	osal Received by Pa	aul Luthi (TECHNICIAN)
Plugging (Operations attended by Agent?: A	IIXPart	None
Operation	s Completed: Hour: 3:30 p.mDay:	28 Month: 9	Year:19 87
ACTUAL PL	ugging REPORT <u>lst plug sanded back</u>	to 3470' and dumped 5 sx	
through du	ump bailer,		
2nd plug j	pumped in 8 5/8" surface casing w	ith 300 lbs. hulls, 10 sx	gel, 50 lbs. hulls,
50 sx ceme	ent, 10 sx gel, 50 lbs. hulls, re	leased 8 5/8" wiper plug a	and pumped 125 sx cement

Pumping pressure 200-300 psi and shut in 100 psi.

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan. Recovered 2072-61, of 5% Casylan.

(Li additional description is necessary, use BACK of this form.)

1 (d hd) ******* observe this plugging.

OCT 5. 1987

gned Duan Rasons

(TECHNICIAN Vichita, Kansas