

15.145.00975.0001

STATE OF KANSAS
STATE CORPORATION COMMISSION
200 Colorado Derby Building
Wichita, Kansas 67202

WELL PLUGGING RECORD
K.A.R.-82-3-117

API NUMBER 5/13/55 (COMPLETED)
LEASE NAME ROBERT BELL
WELL NUMBER 1 SWD
4645 Ft. from S Section Line
165' Ft. from E Section Line
SEC. 34 TWP. 21S RGE. 16 ~~XX~~or(W)
COUNTY PAWNEE
Date Well Completed 5/13/55
Plugging Commenced 11/22/86
Plugging Completed 11/25/86

TYPE OR PRINT
NOTICE: Fill out completely
and return to Cons. Div.
office within 30 days.

LEASE OPERATOR CHEVRON U.S.A. INC.
ADDRESS P.O. BOX 12116, OKLAHOMA CITY, OK 73157
PHONE#(405) 949-7000 OPERATORS LICENSE NO. 4519
Character of Well SWD

(Oil, Gas, D&A, SWD, Input, Water Supply Well)

Did you notify the KCC/KDHE Joint District Office prior to plugging this well? YES

Which KCC/KDHE Joint Office did you notify? DIST #1, DUANE RANKIN

Is ACO-1 filed? NO RECORD If not, is well log attached? YES

DISPOSAL
~~XXXXXXXXXX~~ Formation ARBUCKLE Depth to Top 3975' Bottom 4559' T.D. 4584'

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put in	Pulled out
ARBUCKLE	DISPOSAL	3975	4559	10.75	980'	-0-
				7.00	3975'	-0-
				5.5	4012'	-0-

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from feet to feet each set.

TIH W/BIT TO 4028', PMP 150 BBLS LEASE WATER, NO RETURNS. POOH. TIH W/TRG TO 4001', PMP 100 SX CL "A" CMT, POOH, WOC. TIH & TAG CMT @ 2811' POOH PMP 80 SX CL "A" CMT DN 5-1/2" CSG. CIRC CMT TO SURFACE IN 10-3/4" x 5-1/2" ANNULUS. CUT OFF CSG. CAP & ID WELL.
(If additional description is necessary, use BACK of this form.)

Name of Plugging Contractor N/A License No.

Address

STATE OF OKLAHOMA COUNTY OF OKLAHOMA, ss.

CHEVRON U.S.A. INC. (Employee of Operator) or (Operator) of above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed that the same are true and correct, so help me God.

(Signature) Michael Mc Carthy

(Address) P.O. BOX 12116, OKC., OK 73157

SUBSCRIBED AND SWORN TO before me this 17 day of DECEMBER, 19 86

Steve R. Wilson
Notary Public

My Commission Expires: 9-16-89

12-22-86

DEC 22 1986 Form CP-4
Revised 08-84
CONSERVATION DIVISION
Wichita, Kansas

WELL RECORD

U.S. GEOLOGICAL SURVEY PRINTED IN U.S.A.

WELL NO. **1** LEASE **Robert Bell** COMPANY **Carl G. Corp** A.F.E. **550**
 DATE-DRILLING BEGAN **6-4-54** WELL COMPLETED **8-20-54** FIRST PRODUCTION **Dry**
 SAND RECORD **Dry Hole - Temporarily Abandoned** TOTAL DEPTH **3879'**
 INITIAL PRODUCTION **15.145.009 75.0000**

CASING RECORD

SIZE	WEIGHT	THD	CLASS	MAKE	SET AT DEPTH	BARRELS CEMENT	LES. CAL. ENDS.	PULLED	LEFT IN
10-3/4	•	•	A	•	960	675			960
HOLES: 4 Jts - 32.75' - GR - SS 21 Jts - 29' - HT - SW									

Distance H: 10' from HKB to top of 10-3/4" casing collar.

S- 34 T- 218R- 10W

635	WT			
165	WT			
Pawnee County Kansas				

ELEVATION- DF 1980'

FORMATION RECORD

	FROM	TO
Sand	0	95'
Sh, shells		400
Sh, sd, rd bd		760
Rd bd		974
Anhydrite		1000
Sh, shells		1100
Sh, rd bd		1155
Rd bd, sh		1500
Sh, shells, salt		1690
ln, sh		2395
Broken in		2695
Sh, ln		2820
ln, sh		3215
ln		3395
ln, sh		3484
ln		3775
Sh, ln v/chert		3812
Simpson sh		3865
Sh, sd		3879 TD

WELL RECORD
GULF 7 890-A PRINTED IN U.S.A.

WELL NO. **1** LEASE **Robert Bell** COMPANY **Gulf Oil Corp** A.F.E. **3380**

DATE-DRILLING BEGAN **8-4-54** WELL COMPLETED **8-20-54** FIRST PRODUCTION **Dry**

SAND RECORD **Dry Hole - Temporarily Abandoned** TOTAL DEPTH **3879'**

INITIAL PRODUCTION

CASING RECORD

SIZE	WEIGHT	THD	CLASS	MAKE	SET AT DEPTH	SACKS CEMENT	LBS. CAL. CHLO.	PULLED	LEFT IN
10-3/4	*	*	A	*	980	675			980
NOTE: * 4 jts - 32.75# - 8R - SS 21 jts - 29# - NT - SW									

S- **34** T- **218R-10W**

635' REL			
165' REL			
Pawnee			
County			
Kansas			

Distance H: 10' from HKB to top of 10-3/4" casing collar.

ELEVATION- **DF 1980'**

FORMATION RECORD

	FROM	TO
Sand	0	95'
Sh, shells		400
Sh, sd, rd bd		760
Rd bd		974
Anhydrite		1000
Sh, shells		1200
Sh, rd bd		1455
Rd bd, sh		1500
Sh, shells, salt		1690
Lm, sh		2595
Broken lm		2695
Sh, lm		2820
Lm, sh		3215
Lm		3395
Lm, sh		3484
Lm		3775
Sh, lm w/chert		3812
Simpson sh		3865
Sh, sd		3879 TD