

1 050770

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 145-21,240.0000  
NE NW, SEC. 20, T 20 S, R 19 W  
4620 feet from S section line  
3300 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9427  
Operator: New London/Sharp Engineering  
Name & Address: 708 One Main Place  
Wichita, KS 67202

Lease Name Bender Well # 1  
County Pawnee 141.38  
Well Total Depth 4350 Mississippi feet  
Conductor Pipe: Size feet  
Surface Casing: Size 8 5/8 feet 385

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Red Tiger Drilling Co. License Number 5302  
Address 1720 Kansas State Bank Building, Wichita, KS 67202

Company to plug at: Hour: 3:15 pm Day: 21 Month: February Year: 19 86

Plugging proposal received from Jerb Ogle

(company name) Red Tiger (phone) 316-263-1201  
Elevation 2175'

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1344-86'

1st plug at the base of the Anhydrite with 50 sx cement

2nd plug at 550' with 40 sx cement

3rd plug 30' below the base of the surface pipe with 40 sx cement  
solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by Richard W. Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 5:30 pm Day: 21 Month: February Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 1380' with 50 sx cement, 2nd plug at 480' with 80

sx cement, 3rd & 4th plugs - solid bridge - hulls - plug at 40' -- cement to surface with  
10 sx cement, 5th plug to circulate rat hole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

MAR 4 1986  
3-4-86  
CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel. by Allied.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
If (check) did (not) observe this plugging.

DATE MAR 04 1986

Signed Richard W. Lacey  
(TECHNICIAN)

INV. NO. 12863

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date February 15 1986 month day year

API Number 15- 145-21240

OPERATOR: License # 9427 Name New London/Sharp Engineering Address 708 One Main Place City/State/Zip Wichita, Kansas 67202 Contact Person Mari Rech Phone 265-9825

NE. NW. Sec: 20 Twp: 20 S, Rg: 19 East 4620 Ft. from South Line of Section 3300 Ft. from East Line of Section (Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5302 Name Red Tiger Drilling Co City/State Wichita, Kansas

Nearest lease or unit boundary line 660 feet County Pawnee Lease Name Bender Well # 1 Ground surface elevation ? feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Surface pipe by Alternate: 2 Depth to bottom of fresh water 180 Depth to bottom of usable water 475 Surface pipe planned to be set 370 Projected Total Depth 4300 feet Formation Mississippi

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl X Wildcat Cable

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

cementing will be done immediately upon setting production casing. Date 2/13/86 Signature of Operator or Agent Dennis H. Kern Title Agent

For KCC Use: Conductor Pipe Required 200 feet; Minimum Surface Pipe Required 200 feet per ft. This Authorization Expires 8-12-86 Approved By 2-12-86

Set 370' of 8 7/8 on 2/15/86

Table with columns: PUSHER, TIME, FORMATION, SURFACE PIPE, ANHYDRITE, STARTING TIME & DATE, COMPLETION TIME & DATE, 1st PLUG @, 2nd PLUG @, 3rd PLUG @, 4th PLUG @, RAT HOLE CIRCULATED W/, MUDS HOLE CIRCULATED W/, WATER WELL PLEGGED W/, CEMENT COMPANY, TECHNICIAN. Includes handwritten notes like '5:30 PM', 'Ogle', 'M115 @ 385', '3:15 PM', '5:30 PM 2/2/86', '1380 FT. W/ 50 SX', '480 FT. W/ 80 SX', '40 FT. W/ 5B410 SX', '15 SX', 'Base of Anhydrite 50' x w/40s', '550 surface of pipe w/40s SB & 10s', '15 SX Rathole', '60/40 poz', '6% gel'.

MAR 4 1986