To:	API NUMBER 15-145-21,140 .0000
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION	
200 COLORADO DERBY BUILDING	N SE Corner of
WICHITA, KANSAS 67202	3300 feet from NVXS section line
TECHNICIAN'S PLUGGING REPORT	3300 W SE Corner of feet from MAXXE section line
Operator License # 6420	Lease Name Kelty Well # 1-14
Operator: KRM Petroleum Corporation	County Pawnee
Address 1900 Grant St. Suite 300	Well Total Depth 3964 138.74 feet
Denver, CO 80123	Conductor Pipe: Size feet
	Surface Casing: Size 8 5/8 feet 350
Abandoned Oli Well Gas Well	Input Well SWD Well D&A_X
Other well as hereinafter indicated	
Plugging Contractor Aldebaran Drilling Con	
Address 453 South Webb Road, Suite 100,	, Box 18611, Wichita, KS 67207
Company to plug at: Hour: noon Day:	12 Month: August Year:1984
Plugging proposal received from	Mark Guinn
	(phone) 316-685-5372
were: to fill hole with heavy mud and	l spot cement through drill pipe
1st plug at 1140° with 50 sx cement	
2nd plug at 420 with 60 sx cement solid bridge	
3rd plug hulls - plug at 40' cement to	surface with 10 sx cement
5th plug to circulate rat hole with 10 sx	
oth plug to circulate mouse hole with 10 s	osal Received by leve & Auront (TECHNICIAN)
	(TECHNICIAN)
Plugging Operations attended by Agent?: A	None X
Operations Completed: Hour: <u>2:45 pm</u> Day:_	12 Month: August Year: 1984
ACTUAL PLUGGING REPORT 1st plug at 1140'	with 50 sx cement, 2nd plug at 420' with 60 sx
<u>cement, 3rd &amp; 4th plugs - solid bridge - b</u>	nulls - plug at 40' cement to surface with
10 sx cement, 5th plug to circulate rat ho	ole with 10 sx cement, 6th plug to circulate
mouse hole with 10 sx cement.	
	RECEIVED STATE CORPORATION COMMISSION
	8-14-84 WMISSIO
Remarks: Used 60/40 Pozmix 2% gel 3% cc by	Halliburton
	necessary, use BACK of this forms VATION DIVISION
Mark / (dif not) observe this plugging.	Wichita, Kansas
8-16-84	Signed Steve Quivout
3207	500H 05 =
0	FORM CP-2/3 Rev.01-84