| STATE CORPORATION COMMISSION | |
|---|---|
| | Spot: NESWSWNW Sec/Twnshp/Rge: 24-22S-21E |
| CONSERVATION DIVISION - PLUGG | IG 3080 feet from S Section Line, 4840 feet from E Section Line |
| 266 N. Main St., Ste. 220 | Lease Name: MITCHELL A Well #: 9 W |
| Wichita, KS 67202-1513 | County: LINN Total Vertical Depth: 850 feet |
| Operator License No.: 3728 | String Size Depth (ft) Pulled (ft) Comments |
| Op Name: RJ ENERGY, LLC | PROD 2.875 850 80 SX |
| Address: 22082 NE NEOSHO RD | SURF 7 20 5 SX |
| GARNETT, KS 66032 | |
| Well Type: EOR | C Docket No: E29004.2 Date/Time to Plug: 12/06/2017 12:00 AM |
| Plug Co. License No.: 3728 Plu | Co. Name: RJ ENERGY, LLC |
| Proposal Revd. from: JASON KENT | Company: Phone: (785) 448-4101 |
| Proposed Run down well and pump well Plugging Method: | ıll. |
| Plugging Proposal Received By: | WitnessType: NONE |
| Date/Time Plugging Completed: 12/07 | NOT 8:00 AM KCC Agent: RYAN DULING |
| Actual Plugging Report: | Perfs: |
| Actual Plugging Report: Hooked onto the 2.875" casing at surface | umped water to make sure well would take fluids. In surface to TD. Pressured up well and shut in at ment was reported used to plug this well. RECEIVED KCC DIST # 3 DEC 2 6 2017 CHANUTE, KS |
| Actual Plugging Report: Hooked onto the 2.875" casing at surface Squeezed cement into the 2.875" casing f | umped water to make sure well would take fluids. In surface to TD. Pressured up well and shut in at ment was reported used to plug this well. RECEIVED RCC DIST # 3 DEC 2 6 2017 CHANUTE, KS |
| Actual Plugging Report: Hooked onto the 2.875" casing at surface Squeezed cement into the 2.875" casing f | umped water to make sure well would take fluids. In surface to TD. Pressured up well and shut in at ment was reported used to plug this well. RECEIVED KCC DIST # 3 DEC 2 6 2017 CHANUTE, KS |
| Actual Plugging Report: Hooked onto the 2.875" casing at surface Squeezed cement into the 2.875" casing f | umped water to make sure well would take fluids. In surface to TD. Pressured up well and shut in at ment was reported used to plug this well. RECEIVED RCC DIST # 3 DEC 2 6 2017 CHANUTE, KS |
| Actual Plugging Report: Hooked onto the 2.875" casing at surface Squeezed cement into the 2.875" casing f 400 psi. A total of 30 sacks of portland c | umped water to make sure well would take fluids. In surface to TD. Pressured up well and shut in at ment was reported used to plug this well. RECEIVED RCC DIST # 3 DEC 2 6 2017 CHANUTE, KS |
| Actual Plugging Report: Hooked onto the 2.875" casing at surface Squeezed cement into the 2.875" casing f 400 psi. A total of 30 sacks of portland c | umped water to make sure well would take fluids. In surface to TD. Pressured up well and shut in at ment was reported used to plug this well. RECEIVED RCC DIST # 3 DEC 2 6 2017 CHANUTE, KS |