

1 090357

11-9

15.145.01358.0001  
E-12,417

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- \_\_\_\_\_  
SW NW NW, SEC. 13, T 20 S, R 20 W/E  
4290 feet from S section line  
4950 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6239

Lease Name Jennings C Well # 1

Operator: Zinszer Oil Company, Inc.

County Pawnee

Name & Address P.O. Box 211

Well Total Depth 4350 141.37 feet

Hays, KS 67601

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 495

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well X SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Zinszer Oil Company, Inc. License Number 6239

Address P.O. Box 211, Hays, KS 67601

Company to plug at: Hour: 5 p.m. Day: 9 Month: 11 Year: 1993

Plugging proposal received from Perry Henman

(company name) Zinszer Oil Co., Inc. (phone) 913-625-9448

logs: 5 1/2" at 4265', Perfs at 4178-86' squeezed with 75 sx cement

1st plug hook onto 5 1/2" casing and pump in 375 sx cement,

2nd plug hook onto backside and pump in 60 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 5:45 p.m. Day: 9 Month: 11 Year: 1993

ACTUAL PLUGGING REPORT 1st plug hooked onto 5 1/2" casing and pumped in 375 sx cement.

Maximum pressure 650 psi and shut in 400 psi.

2nd plug hooked onto backside and pumped in 60 sx cement. Maximum pressure 400 psi and shut in 150 psi.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton. No casing recovery.

(If additional description is necessary, use BACK of this form)

I (did/did not) observe this plugging.

DATE 12-9-93

INV. NO. 39434 11-9 JAN 11 1994

Signed \_\_\_\_\_ (TECHNICIAN)

RECEIVED STATE CORPORATION COMMISSION NOV 16 1993 CONSERVATION DIVISION Wichita, Kansas