

KANSAS

FORM CP-3
Rev. 1-8-82

STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT REPORT

API Number 15-145-20,833

200 Colorado Derby Building
Wichita, KS 67202

Operator's Full Name Anador Resources, Inc.

Complete Address 5700 S. Quebec Suite 320 Englewood Co.

Lease Name Bryant Well No. 1-8 80111

Location C NW Sec. 8 Twp. 21 Rge. 18 (East)(West)

County Pawnee Total Depth 2305

Abandoned Oil Well Gas Well Input Well SWD Well D&A

Other well as hereinafter indicated _____

Plugging Contractor Sun Cementing

Address Grent Bend Rd. 67530 License No. _____

Operation Completed: Hour: 11:30 AM Day: 13 Month: 8 Year: 19 82

Plugging Operations attended by Agent?: All Part None

The above well was plugged as follows:

7" S.P @ 980' w/ cement luv.

no paper, ect.

Plug: 2 5x bulls → 5 5x gel →
160 5x cement

Max pump pressure 500 #

Shut in @ 300 #

cm by Sun

Amount of Surface Casing: 980'

I hereby certify that the above plugging instructions were given as herein stated.

Signed: Steve Wilmont
Conservation Division Agent

I hereby state that I was not present while the above well was being plugged, however, to the best of my knowledge and belief it was plugged as herein stated. A full account for my not being present is as follows:

INVOICED
9-1-82
DATE _____
INV. NO. 999-W

STATE CORPORATION COMMISSION
RECEIVED
AUG 25 1982
Signed _____ Conservation Division Agent
CONSERVATION DIVISION
Wichita, Kansas

15.145.20833.0000

Sun Oilwell Cementing
A Division of BJ Hughes, Inc.

P. O. Box 169
GREAT BEND, KANSAS 67530

CEMENTING TICKET No 12927
and Invoice Number

Date 8-13-82	Customer Order No.	Sec	Twp.	Range	Truck Called Out 6:30AM	On Location 9:10AM	Job Began 11:00AM	Job Completed 11:30AM
Owner Anador Resources		Contractor			Charge To Anador Resources			
Mailing Address		City			State			
Well No. and Farm Bryant #1-8		Place 163 & 156 Jct. W. 117th St			County Pawnee		State Ks.	
Depth of Well	Depth of Job	Casing Used	Size 7"	Weight	Size of Hole Amt. and Kind of Cement 160sx	Cement Left in casing by	Request Necessity	feet
Kind of Job Plug to Abandon					OW	Drillpipe	Rotary	Truck No. #31
					NW	Tubing	Cable	
Condition of well at time of Cementing					Type of Plugs Wooden Rubber Cyp			
Pressure Circulating		Minimum		Maximum				
Time Required Mixing Cement		min.		Making Change		min.		Pumping Cement
								min.

Remarks: Mixed 2sx Halls, 5sx gel., 160sx 50/50 Poz, 390 Cal. 490 Gel. with plug released between Gel. & Cement. Mixing pressure 500PSI, Shut In Pressure 300PSI.

#9
Price Reference No.
Price of Job 370.00
Second Stage
Standby Truck
Other Charges
Pump Truck Mileage 58.50

Thanks

Cement: Barry Dale
Material Left on Location: 7" P.C. & Manifold
Helper: Dale
District: G. Bend
State: Ks.
The above job was done under supervision of the owner, operator, or his agent whose signature appears below.
X
Agent of Contractor or Operator

Prices Subject to Correction.

SALES TICKET FOR MATERIALS

QUANTITY SACKS	BRAND AND TYPE	PRICE	TOTAL
80	5x Com	4.80	384.00
80	5x Poz.	1.90	152.00
200	Halls	14.00	28.00
Cc Cl.	403#	.21	84.63
AM. Cl.	1038#	.061	63.32
Gel	7" WOODEN Rubber Cyp	30.00	30.00
Plugs			
	Delivered by Truck No. B. 25	160 Handling and Dumping	.92 147.20
	Delivered From G. Bend	7.5 Mileage 39	1.68 198.90
	Signature of Operator Karl	Sales Tax	45.50
		Total Charges	202.05

STATE RECEIVED
CONSERVATION COMMISSION

AUG 24 1982
CONSERVATION DIVISION
Wichita, Kansas