	ı 040049				
To: STATE CORF	PORATION COMMISSION	API NUMBER 15-	185-22,024	.0000	
CONSERVATION DIVISION - PLUGGING SECTION E 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 TECHNICIAN'S PLUGGING REPORT		E/2 NE NW, SEC.		21 s, R 1	<u>2_</u> ₩/₭
		4620	feet from	S section	n Ilne
					n Ilne
Operator L	License / 6039	Lease Name Sayl	er w	ell #1	
Name& Address	L.D. Davis dba L.D. Drilling, Inc		fford		6.09
	Rt. 1, Box 183B	Well Total Dept	h 3572	2	feet
	Great Bend, KS 67530	Conductor Pipe:			
		Surface Casing:			
Lhandoned	011 Well Gas Well			-	
			_ 310 11011_		
	as hereinafter indicated	T		6050	
	Contractor Kelso Casing Pulling, 1	Inc.	License Nu	mber	
	ox 347, Chase, KS 67524				
	o plug at: Hour: 3 p.m. Day:			Year:19	
	proposal received from Clay Duntz		 	<u> </u>	
(company r	name) Kelso Casing Pulling, Inc.		(pho	ne)_316-938-	-2457
*ere: 5½"	at 3562' Open hole 10' below cas:	ing	<u> </u>	<u> </u>	
Ist plug	sand back to 50' below casing with	5 sx cement on to	op of sand	through bai	ler,
2nd plug	pump 4 sx hulls, 10 sx gel, 50 sx	cement, 10 sx gel,	, 1 sx hull	s, release 8	3 5/8 "
	g and pump 100 sx cement.				
	Plugalna Propos	sal Received by I	Richard Lac		
			(TEC	HNICIAN)	
Flugging (Operations attended by Agent?: All	X Part_		None	_ .
	s Completed: Hour: <u>3:30 p.m</u> .Day:			_ 1001.17	38
ACTUAL PL	UGGING REPORT 1st plug sand back	to 3510' and dump	5 sx cemen	t on top of	sand
hrough ba:	iler,				
2nd plug	pumped down 8 5/8" with 400 lbs. h	ulls, 10 sx gel,	50 sx cemen	t, 10 sx ge	1, 100 11
hulla ro	leased 8 5/8" wiper plug and pumpe	d 100 sx cement.			
mir is, is	reasen o 570 wiper plus and pompe	200 511 00	CTATE	Carabanum J.	Onesion.
Maximum p	pressure 400 psi and shut in 50 psi	. 2	-8-98	FEB 0 8 198	3
Remarks	Used 60/40 Pozmix 6% gel by Allied		<u> </u>	saing . Hun drus	ION
	(If additional description is n	necessary, uso BAC	K of this f	orm.)	
1 19 7 C	the diserve this plugging.	0 /	211	$1 \cdot \bigcirc 1 \cdot 0$	A.
_	· · · · · · · · · · · · · · · · · · ·	Signed Sto	is hom) (. 41.11.)

FORM CP-2/3 Rev.01-84