CONSERVAT	1010076  PORATION COMMISSION ION DIVISION - PLUGGING SECTION ADO DERBY BUILDING KANSAS 67202	Docket No. E-06,115 - Docket No. still Active   5-145-01389-60-01  API NUMBER 15- Completed 12-22-52  SW SW NW , SEC. 32 , T 23 s, R 15 W/K  2970 feet from S section line
TECHNICIAN'S PLUGGING REPORT 2970 feet from E section line		
Operator License 5 5447 Lease Name Benson Unit Well 206W		
Operator: Name& Address	Cities Service Oil & Gas Corp.	County Pawnee 125.78
	3545 NW 58th Street	Well Total Depthfeet
	Oklahoma City, OK 73112	Conductor Pipe: Sizefeet
		Surface Casing: Size 8 5/8 feet 369
Abandoned	Oli Well Gas Well	Input Well D&A
Other well as hereinafter indicated		
Plugging (	Contractor Kelso Casing Pulling	License Number 6050
Address P. O. Box 347, Chase, KS 67524		
Company to piug at: Hour: 1:15 pm Day: 21 Month: January Year:19 86		
Plugging proposal received from Neil Peddicord		
(company name) Kelso (phone) 316-938-2457		
were: 5 1/2" at 3870' PBTD 3674' Perfs at 3603-3612'  1st plug sand back to 3550' and dump 5 sx cement on top of sand through bailer		
2nd plug squeeze well with 3 sx hulls, 15 sx gel, 50 sx cement, 10 sx gel, 1 sack hulls,		
release 8 5/8" rubber plug and pump 150 sx cement.		
Plugging Proposal Received by Richard W. Lacey (TECHNICIAN)		
Plugging Operations attended by Agent?: All X Part None		
Operations Completed: Hour: 1:45 pm Day: 21 Month: January Year:19 86		
ACTUAL PLUGGING REPORT 1st plug sanded back to 3550' and dump 5 sx cement on top of		
sand through bailer, 2nd plug squeezed well with 3 sx hulls, 15 sx gel, 50 sx cement, 10 sx		
gel 1 sack hulls, released 8 5/8" rubber plug and pumped 150 sx cement.		
HELETY EU STATE CORPORATION COMMISSION		
		1-27-86JAN 27 1986
Maximum pr	ressure 300 psi and shut in 200 p	conservation division
Remarks: Recovered 2500' 5 1/2" casing. Used 60/40 Pozmix 6% gel by Allied.		
(If additional description is necessary, use BACK of this form.)  Vold September observe this plugging.  FEB 5 1986 (TECHNICIAN)		
NO. 12334 1-21 FORM CP-2/3 Rev.01-84		