

15-009-22943-00-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15

SW, Sec. 16, T 16 S, R 12 W/E  
990 feet from S section line  
1650 feet from W section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5770

Lease Name Kriem Well # 1 R

Operator: Reif Oil Operations, Inc.  
Name & Address: P.O. Box 298, Hainington, Mo. 67544

County Barton  
Well Total Depth 3402' feet \$ 110.57

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8" feet 331

Abandoned Oil Well X Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor D. S. & W. Well Servicing, Inc. License Number 6901

Address Box 231, Claplin, Mo. 67825

Company to plug at: Hour: 11:00AM Day: 3 Month: 3 Year: 1983

VERBAL PLUGGING ORDERS GIVEN TO Don Reif

(company name) Reif Oil Operations, Inc. (phone) 316-653-7745

were: Order 165 lbs. 50% perme - 4% Gel. - 3% Cal. Cl., 5 sh. balls, 15 sh. Gel. & 8 5/8" plug.

Signed [Signature]  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 11:00AM Day: 3 Month: 3 Year: 1983

ACTUAL PLUGGING REPORT 8 5/8" - 331' SP. inc. w/ 200 sh. cement. 4 1/2" set at 3401' w/ 200 sh. Top perf at 2746'. Plugged bottom w/ 5 sh. cement, sand + 5 sh. cement. Shot pipe 1 time & recovered 2100'. Pumped in 8 5/8" SP. 4 sh. balls, 12 sh. Gel. 65 sh. cement, 3 sh. Gel, 1 sh. balls, released plug & Followed w/ 100 sh. cement.

Maximum pressure 800 pounds

Remarks: \_\_\_\_\_

RECEIVED  
STATE CORPORATION COMMISSION

MAR 14 1983  
3-14-83

CONSERVATION DIVISION  
Wichita, Kansas

I hereby certify that the above plugging instructions were given as herein stated

and that I (did / did not) observe this plugging.

INVOICED

DATE 4-4-83  
INV. NO. 3819-W

Signed [Signature]  
(TECHNICIAN)