

1 050609

R

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-075-20,204.0000  
50'N 50'W of Ctr. or  
SE SE NW, SEC. 12, T 21 S, R 40 W/X

2690 feet from S section line  
2690 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9392  
Operator: Monarch Energy Corp.  
Name & Address: P. O. Box 6  
Liberal, KS 67901

Lease Name Almquist Well # 1  
County Hamilton 91.81  
Well Total Depth 2825' feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 348

Abandoned Oil Well \_\_\_\_\_ Gas Well X Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Allied Cementing License Number \_\_\_\_\_  
Address North Highway 283, Ness City, KS 67560

Company to plug at: Hour: 10:00 am Day: 15 Month: August Year: 1985

Plugging proposal received from Terry Maxwell  
(company name) Consultant for Monarch (phone) 316-624-3767

were: 4 1/2" at 2825' PBTD 2820' Perfs at 2767-2777

Squeeze well with 2 sx hulls, 40 sx cement, 6 sx gel and 100 sx cement

Plugging Proposal Received by Richard W. Lacey  
(TECHNICIAN)  
Clyde Wiley observed this plugging

Plugging Operations attended by Agent?: All x Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:45 am Day: 15 Month: August Year: 1985

ACTUAL PLUGGING REPORT Squeezed well with 2 sx hulls, 40 sx cement, 6 sx gel and 70  
sx cement.

Maximum pressure 1100 psi

Remarks No Recovery, Used 60/40 Pozmix 6% gel by Allied. Cement Circ on 4 1/2"  
(If additional description necessary, use BACK of this form.)  
Clyde Wiley observed this plugging  
(If not observed) observe this plugging.

INVOICED

RECEIVED

DATE AUG 28 1985

AUG 28 1985

Signed Richard W. Lacey  
(TECHNICIAN)

INV. NO. 9827

CONSERVATION DIVISION  
Wichita, Kansas