

To: 1 031394
STATE CORPORATION COMMISSION
Wichita State Office Bldg. - PLUGGING SECTION of W/2 NE SW, SEC. 13, T 21 S, R 43 W/E
130 S. Market, Room 2078
Wichita, KS 67202

API NUMBER 15- 075-20,581.0000
112' N & 63' W
2092 feet from S section line
1587 feet from WE section line

TECHNICIAN'S PLUGGING REPORT 4-17
Operator License # 7873
Operator: Ricks Exploration, Inc.
Name & Address: 5600 N. May Ave., Ste. 350
Oklahoma City, OK 73112

Lease Name Burge Well # 13A
County Hamilton
Well Total Depth 6690 217.42 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 1500

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X
Other well as hereinafter indicated _____

Plugging Contractor BEREDCO, Inc. License Number 5147
Address 401 E. Douglas, Wichita, KS 67202

Company to plug at: Hour: 8 a.m. Day: 17 Month: 4 Year: 1996

Plugging proposal received from Everett Lesburg
(company name) Ricks Exploration Inc. (phone) 405-340-9099

purpose: to fill hole with heavy mud and spot cement through drill pipe
1st plug at 4700' with 50 sx cement, 2nd plug at 2400' with 50 sx cement,
3rd plug at 1500' with 25 sx cement, 4th plug at 690' with 25 sx cement,
5th plug at 40-0' with 15 sx cement, 6th plug to circulate rathole with 15 sx cement,
7th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Durrant
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 1:30 p.m. Day: 17 Month: 4 Year: 1996

ACTUAL PLUGGING REPORT 1st plug at 4660' with 50 sx cement,
2nd plug at 2480' with 50 sx cement, 3rd plug at 1500' with 25 sx cement,
4th plug at 690' with 25 sx cement,
5th plug at 40-0' with 10 sx cement,
6th plug to circulate rathole with 15 sx cement,
7th plug to circulate mousehole with 10 sx cement.

RECEIVED
KANSAS CORPORATION COMMISSION
APR 19 1996
4-19-86
CONSERVATION DIVISION
WICHITA, KS

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.
(if additional description is necessary, use BACK of this form.)

INVOICED
I hereby certify that I have observed this plugging.

DATE APR 23 1996

Signed Steve Durrant
(TECHNICIAN)

INV. NO. 45-383
4-17

EFFECTIVE DATE: 3-26-96

State of Kansas

FORM MUST BE TYPED

DISTRICT # 1

NOTICE OF INTENTION TO DRILL 075-20,581

FORM MUST BE SIGNED

SGA? Yes X No

Must be approved by the K.C.C. five (5) days prior to commencing well.

ALL BLANKS MUST BE FILLED

Expected Spud Date 3 25 96 month day year

Spot 112' N 63' W OF W/2 - NE SW Sec 13 Twp 21S S, Rg 43W East West

OPERATOR: License # 7873 Name: Ricks Exploration, Inc. Address: 5600 No. May Ave., Suite 350 City/State/Zip: Oklahoma City, OK 73112 Contact Person: Lynne Suchy/Jeff Nelson Phone: 405/340-9099

2092' feet from South / North line of Section 1587' feet from East / West line of Section IS SECTION X REGULAR IRREGULAR?

CONTRACTOR: License #: 5748 5147 Name: BEREDCO

(NOTE: Locate well on the Section Plat on Reverse Side) County: Hamilton

Well Drilled For: Well Class: Type Equipment: X. Oil ... Enh Rec ... Infield X. Mud Rotary X. Gas ... Storage ... Pool Ext. ... Air Rotary ... OWWO ... Disposal ... Wildcat ... Cable ... Seismic; ... # of Holes ... Other

Lease Name: BURGE Well #: 13A Field Name: Wildcat

If OWWO: old well information as follows: Operator: Well Name: Comp. Date: Old Total Depth

is this a Prorated/Spaced Field? ... yes ..X no Target Formation(s): Mississippi

Directional, Deviated or Horizontal wellbore? ... yes ..X no If yes, true vertical depth: Bottom Hole Location:

Nearest lease or unit boundary: 1587' Ground Surface Elevation: 3798.2 feet MSL

Exp. 9/21/96

Water well within one-quarter mile: ... yes ..X no Public water supply well within one mile: ... yes ..X no

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq. It is agreed that the following minimum requirements will be met:

Depth to bottom of fresh water: 500' Depth to bottom of usable water: 900' 1750'

Surface Pipe by Alternate: X 1 2 Length of Surface Pipe Planned to be set: 1500' Length of Conductor pipe required: 40' - 0'

Projected Total Depth: 6800' Formation at Total Depth: Arbuckle

Water Source for Drilling Operations: ... well ... farm pond X other

Will Cores Be Taken? ... yes ..X no If yes, proposed zone:

1280' Alt. I Req.

It is agreed that the following minimum requirements will be met:

RECEIVED KANSAS CORPORATION COMMISSION

58,000 mud pill - RECEIVED KANSAS CORPORATION COMMISSION

EVERETT LESBURG

Pusher

SPUD DATE 3-25-96 INIT. [Signature]

LENGTH SURFACE PLANNED 1100'

RESERVE PIT STATUS- REMOVE FLUID LINED after salt sect. bbls. when done bbls.

RATHOLED AHEAD? Y N SIZE HOLE SURFACE PIPE 8 5/8 @ 1500 CONDUCTOR ANHYDRITE T B ELEVATION

TD 6690 FORMATION 160 SX - 4550 4900 6 1/4" hole-Nitrogen blow-out @ 1800' ALT II DONE

Arbuckle Plug @ 4900 Ft. W/ 50 SX SX

Plug./Council @ 4800 Ft. W/ 50 SX SX

Anhydrite Base @ 480 Ft. W/ 50 SX SX

1/2 Base Anyh. @ 1500 Ft. W/ 25 SX SX

1/2, 1/2 Plug @ 690 Ft. W/ 25 SX SX

Bottom Surface @ 40-0 Ft. W/ 10 SX SX

40' Plug @ 40-0 Ft. W/ 10 SX SX

RAT HOLE PRESSURE IN 8 5/8 X 7' annular CIRC/W SX MOUSE HOLE W/ 10 SX SX

WATER WELL 15 SX (Irr. Well Pond Hauling)

TECHNICIAN H3AVUL DATE 4-17-96

TYPE OF CEMENT 60/40 Port 60/0

STARTING TIME 8:00 (AM/PM) DATE 4-17-96

COMPLETION TIME 1:30 (AM/PM) DATE 4-17-96

CEMENT COMPANY Holl-buckton

APR 19 1996

CONSERVATION DIVISION WICHITA KS