,	•	ADI NUMBER 18. 185-22.052.00	od/×
To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION C 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		API NUMBER 15- 185-22,052-0000	
		/2 <u>NW NE</u> , SEC. 20	\$, R <u>13</u> \#/& Corner of
		4620 (5) feet from N	KSK section line
TECHNICIAN'S PLUGGING REPORT		1650 (EV feet from 数	Corner of Scinion line
Operator L	Icense / 5230	Lease Name Fanshier 'A' Well	1 1
	Petroleum Energy, Inc.	County Staf	ford
Nemox	415 First National Bank Bldg.	CountyStaf Well Total Depth3689	119,89,001
	Wichita, KS 67202	Conductor Pipe: Size	
		Surface Casing: Size 8 5/8	feet 343
Abandoned	Oli WellGas Well	Input WellSWD Well	D&AX
Other Well	l as hereinafter indicated		
	Contractor White & Ellis Drilling		
	401 East Douglas, Wichita, KS 67		
	plug at: Hour: 12:00 noonDay: 2		
Plugging (proposal received from	udy Steiben	
(company r	white & Ellis -Great Be	ad (phone)	316-692-2424
were:	to fill hole with heavy mud and	spot cement through drill pipe	
1st plug a	at 810° with 50 sx cement		
2nd nlug s	at 390' with 40 sy cement		
	at 390' with 40 sx cement solid bridge		
	nulls - plug at 40' cement to s		
	to circulate rat hole with 15 sx cor r well with 5 sx cement		
	Plugging Propo	sal Received by Say Churon (TECHN	101411
-	Operations attended by Agent?: Al		
Operation:	s Completed: Hour: $2:45 \text{ pm}$ Day; $2:45 \text{ pm}$	4 Month: August Y	ear:19 <u>84</u>
ACTUAL PL	ugging REPORT 1st plug at 810° with	1 50 sx cement, 2nd plug at 390	with 40 sx
cement, 31	rd & 4th plugs - solid bridge - hu	lls - plug at 40' cement to	surface with
10 sx ceme	ent, 5th plug to circulate rat hold	e with 15 sx cement, and plugged	d water well
with 5 sx	cement.		 ,,-
			 _
			
Remarks: \	Used 60/40 Pozmix 2% gel 3% cc by 1	Sun	
	(If additional description is	necessary, use BACK of this for	n•)
11 (4) 47 1	operation this spategarage tion	COMMISSION	
		1984 Signed Serie Church	a she
re 9-1	1-01		
NO. 36	CONSERVATION D Wichita, Kans		FORM CP-2/3 Rev.01-84