

TO:

STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
266 N. Main St., Ste. 220
Wichita, KS 67202-1513

API Well Number: 15-019-19440-00-00

Spot: SESENWNW Sec/Twnshp/Rgc: 5-35S-13E
4041 feet from S Section Line, 4222 feet from E Section Line

Lease Name: J R HYDER-STEINBERGER U Well #: 13

County: CHAUTAUQUA Total Vertical Depth: 750 feet

Operator License No.: 32255

Op Name: KANSAS ENERGY COMPANY, L.L.C.

Address: BOX 68
SEDAN, KS 67361

String Size Depth (ft) Pulled (ft) Comment

PROD 6 750 0 SX

SURF 10 40 0 SX

Well Type: OIL

UIC Docket No:

Date/Time to Plug: 06/25/2017 12:00 AM

Plug Co. License No.: 32884

Plug Co. Name: ELMORE'S, INC.

Proposal Rcvd. from: P.J. BUCK

Company:

Phone: (620) 725-3636

Proposed
Plugging
Method:

Surface cement unknown. Run 1" to TD. Gel hole. Spot 50' plug of cement on bottom. Spot 50' plug of cement at 700'. Pull up to 350' and cement to surface.

Plugging Proposal Received By: DUANE SIMS

Witness Type: PARTIAL

Date/Time Plugging Completed: 06/26/2017 12:00 AM

KCC Agent: DUANE SIMS

Actual Plugging Report:

Contractor fished out tubing and perforated casing at 640'. Spotted bottom plug at 640'. Well was still leaking brine up casing. Operator ran 2 1/2" liner with rag packer to 300'. Ran down backside of 2 1/2" with 1" and spotted cement. Came back next day and still had brine leaking up inside and outside of casing. Injection system was shut down and 40 sacks of weight mud was pumped down 2 1/2" casing. Leaking brine was shut off. Ran 1" to 150' down backside of 2 1/2" and circulated cement to surface. Hooked on to 2 1/2" liner and squeezed 130 sacks of cement down liner and into well bore. A total of 270 sacks of cement were used to plug this well,

Perfs:

Top	Bot	Thru	Comments
700	710		
RECEIVED KCC DIST # 3 AUG 22 2017 CHANUTE, KS DS			


Remarks: WELL WAS PLUGGED DUE TO PLUGGING AGREEMENT SIGNED BY OPERATOR WITH THE KCC! **VOICED**

Plugged through: TBG

AUG 31 2017

District: 03

Signed



(TECHNICIAN)