

1080001 15.083.20524.0000

To: STATE CORPORATION COMMISSION  
Wichita State Office Bldg. PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, KS 67202

API NUMBER 15- Docket #D-19,056  
SE NW SW, SEC. 11, T 21 S, R 25 W/X  
1650 feet from S section line  
4290 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 4058  
Operator: American Warrior, Inc.  
Name & Address: P.O. Box 399  
Garden City, KS 67346

Lease Name Grass Well # 1  
County Hodgeman  
Well Total Depth 1301 42.28 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 313

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well X O&A \_\_\_\_\_  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Plains Inc. License Number 5287  
Address P.O. Box 346, Ness City, KS 67560

Company to plug at: Hour: 3:30 p.m. Day: 6 Month: 12 Year: 19 95

Plugging proposal received from Scott Corsair  
(company name) American Warrior, Inc. (phone) 913-398-2270

Work: 4 1/2" at 1300' w/300 sx cement, PBTB 1299', Perfs at 1162-1236'  
1st plug pump 25 sx cement at perfs,  
2nd plug pump 400 lbs. hulls and 100 sx cement.

Plugging Proposal Received by Kevin Strube (TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 4 p.m. Day: 6 Month: 12 Year: 1995

ACTUAL PLUGGING REPORT 1st plug pumped 25 sx cement out into perfs,  
2nd plug pumped down 4 1/2" - injection rate 350 psi, 1 1/2 bbl. per minute with 400 lbs. hulls,  
85 sx cement. Maximum pressure 1000 psi and shut in 900 psi.

RECEIVED  
STATE CORPORATION COMMISSION  
DEC 13 1995  
CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton. No casing recovery.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
(If additional description is necessary, use BACK of this form.)  
observe this plugging.

Signed X Kevin D Strube (TECHNICIAN)

DATE 12-13-95  
INV. NO. 44350  
12-6