

9-23

4-071062

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15-009-24,431-0000

E2 SE NE /4 SEC. 25, 20 S, 15 W
3390 feet from S section line
1650 feet from E section line

Operator license# 5591 Lease Brining well # B-1

Operator: Wes Tech Energy Co., Inc. County Barton

Address: P.O. Box 949 Well total depth 3632 feet 118.04
Great Bend, Kansas 67530 Conductor Pipe: 0 inch @ 0 feet
Cathy Pekarek Surface pipe 8 5/8 Inch @ 871 feet

Aband. oil well X, Gas well, Input well, SWD, D & A

Plugging contractor: D.S. & W. Well Service - Allied Cement License#

Address: Claflin, Kansas - Great Bend, Kansas

Company to plug at: Hour: P.M. Day: 23 Month: September Year: 93
Plugging proposal received from: Gary Burke

RECEIVED
STATE CORPORATION COMMISSION
SEP 29 1993
CONSERVATION DIVISION
Wichita Kansas

Company: D.S. & W. - Great Bend Casing Phone: 316-792-5653

Were: 8 5/8" - 871' cwc. w/350 sxs. cement. 5 1/2" casing set @ 3626'
w/125 sxs. cement. Elv. 1910' - Anhy. 856' - Perf. open hole 3626' -
3632'. Casing good. Proposal 250 sxs. 60/40 pozmix - 8% gel. - 8 sxs.
gel on the side. Sand bottom to 3515' then 5 sxs. cement. Shot casing @
2700' - 2579' - 2487'. Pump in with pump truck, spot and displace cement
through 5 1/2" casing - 35 sxs. @ 1687' - 45 sxs. @ 917' - 8 sxs. gel
@ 688' - 75 sxs. @ 315'. Pull 5 1/2" then fill 8 5/8" S.P. to cellar.

Plugging Proposal Received by: Herb Deines
Plugging operations attended by agent? All [X], Part [], None []

Completed: Hour: 3:30 P.M., Day: 23, Month: September, Year: 93

Actual plugging report: Wes Tech ordered 250 sxs. 60/40 pozmix - 8% gel
8 sxs. gel on the side. Pumped in with pump truck, spotted and displaced
all cement and gel through 5 1/2" casing. Sand bottom to 3515' - Shot
5 1/2" casing @ 2700' - 2579' - 2497'. 1) Spot and displace 35 sxs.
cement @ 1687'. 2) Spot and displace 45 sxs. cement @ 917'. 3) Spot and
displace 8 sxs. gel @ 688'. 4) 5 1/2" casing @ 315' w/75 sxs. cement.
Cement circulated - Laid down 5 1/2" casing and filled 8 5/8" S.P. to
cellar with cement.

Remarks: By: Allied Cement.
Condition of casing(in hole): GOOD X BAD Anhy. plug: YES X NO
Bottom plug(in place): YES X, CALC, NO Dakota plug: YES X, NO
Plugged through TUBING, CASING X. Elevation: 1910 GL

I did not observe the plugging. *mperson*

INVOICED
DATE OCT 05 1993
SERV. NO. 38870

(agent)
Form CP-2/3