

To: 1 051202  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

9-1  
API NUMBER 15-145-21,101,0000  
C SW SW, SEC. 6, T 20 S, R 19 W/E  
660 feet from S section line  
4620 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 4477  
Operator: Double T Oil Company, Inc.  
Name & Address: P.O. Box 906  
Hooker, OK 73945

Lease Name Price Well # 1  
County Pawnee 141.15  
Well Total Depth 4343 feet  
Conductor Pipe: Size feet  
Surface Casing: Size 8 5/8 feet 260

Abandoned Oil Well X Gas Well Input Well SWD Well D&A

Other well as hereinafter indicated

Plugging Contractor McPherson Drilling License Number 5495  
Address Route 2, Box 168D, Augusta, KS

Company to plug at: Hour: 12:15 p.m. Day: 1 Month: 9 Year: 19 89

Plugging proposal received from Bill McPherson  
(company name) McPherson Drilling (phone) 316-221-3560

were: 5 1/2" at 4342' Perfs at 4294-96'

1st plug sand back to 4240' and dump 5 sx cement on top of sand through bailer,  
2nd plug pump 3 sx hulls, 6 sx gel, 60 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  
wiper plug and pump 125 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION  
SEP - 0 1989

Plugging Proposal Received by Steve Durrant (TECHNICIAN)

Plugging Operations attended by Agent?: All X Part None

Operations Completed: Hour: 1:15 p.m. Day: 1 Month: 9 Year: 19 89

ACTUAL PLUGGING REPORT 1st plug sanded back to 4240' and dumped 5 sx cement on top of sand through bailer,

2nd plug pumped 3 sx hulls, 6 sx gel, 60 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  
wiper plug and pumped 125 sx cement.

Maximum pressure 700 psi and shut in 600 psi.

Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 1963' of 5 1/2" casing.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
(If additional description is necessary, use BACK of this form.) observe this plugging.

DATE 9-13-89

Signed Richard W. Lacy (TECHNICIAN)

INV. NO. 25887

NOV 06 1989 FEB 09 1990

FORM CP-2/3 Rev. 01-84