

STATE OF KANSAS
STATE CORPORATION COMMISSION

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bittling Building
Wichita, Kansas

WELL PLUGGING RECORD

Barton County, Sec. 13 Twp. 20S Rge. 15W (E) (W)

Location as "NE/CNW/SW" or footage from lines NE SW SE

Lease Owner The Son Construction Company

Lease Name L. L. Gunn Well No. 1

Office Address Chase, Kansas

Character of Well (completed as Oil, Gas or Dry Hole) Oil Well

Date well completed October 4 19 45

Application for plugging filed August 24 19 55

Application for plugging approved August 26 19 55

Plugging commenced August 24 19 55

Plugging completed August 29 19 55

Reason for abandonment of well or producing formation Depleted.

If a producing well is abandoned, date of last production July 19 55

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well Warren H. Horner

Producing formation _____ Depth to top _____ Bottom _____ Total Depth of Well 3650 Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				9-5/8"	877'	None
				7" OD	3627'	1890'
				Hole was plugged back to 3618' and casing perforated from 3596' to 3618'.		

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Filled the hole with sand from 3618' to 3585' and ran 5 sacks of cement. Mudded the hole to 310', set a 10' rock bridge and ran 25 sacks of cement at 300'. Mudded the hole to 30' and ran 10 sacks of cement on top. Plugging comp.

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor West Supply Co., Inc.
Address Chase, Kansas

STATE OF Kansas COUNTY OF Rice, ss.

Robert A. Halpelt (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) Robert A. Halpelt - owner

Chase, Kansas (Address)

SUBSCRIBED AND SWORN TO before me this 6th day of September, 19 55

Thomas V. Higgins Notary Public.

My commission expires Sept. 27, 1958

RECEIVED
STATE CORPORATION COMMISSION

PLUGGING
FILE SEC 13 T 20 R 15W
BOOK PAGE 145 LINE 9

9-8-1955

15.009.05721.0000

WELL NO. 1 LEASE L. H. Gunn COMPANY Gulf Oil Corporation A.F.E. 2470
 DATE—DRILLING BEGAN 8-6-45 WELL COMPLETED 10-11-45 FIRST PRODUCTION —
 SAND RECORD Arbuckle lime 3596' - 3618' TOTAL DEPTH 3618'
 PB from 3650'

INITIAL PRODUCTION (Well temporarily abandoned. May possibly recomplete as gas well)

CASING RECORD

S-13 T-208 R-154

SIZE	WEIGHT	THD.	CLASS	MAKE	SET, AT DEPTH	BACKS CEMENT	LBS. CAL. CHLO.	PULLED	LEFT IN
9 5/8"	40	8V	B	Sm. St.	885'	400			877'
7"	24	"	B	Sm. St.	3630'	100			3627'

Center				
WM				
ST				
ES				
Warton				
County				
Kansas		o		

79 jts. 10V thd; 1 jt. 10V & 8R thd; 57 jts. 8R thd.


RT 8' above top collar on 9 5/8" csg.
 RT 3' above top collar on 7" csg.

ELEVATION - 1916'

AGILIZED: 9-6-45 with 1000 gallons 3639' - 3640'
 ACIDIZED: 10-3-45 with 1000 gallons 3635' - 3638'

FORMATION RECORD:

From	To	Description
0'	60'	Sand
	195	Sand, shale and shells
	340	Shale and shells
	390	Sand
	465	Red bed and shale
	590	Sand, shale and shells
	605	Shale and shells
	700	Red sand, rock and red bed
	795	Red bed and sand
	868	Red bed and shale
	885	Anhydrite and shale
	907	Anhydrite
	955	Shale and red bed
	1275	Shale and shells
	1645	Salt, shale and shells
	1705	Shale and shells
	1765	Lime, broken
	1855	Lime
	2015	Lime, broken
	2075	Lime, sandy
	2300	Lime and shale
	2375	Lime, broken
	2390	Shale and shells
	2480	Lime and shale
	2620	Lime
	2730	Lime and shale
	2755	Lime
	2820	Lime, shale and lime
	2900	Lime and shale
	3391	Lime
	3421	Porous lime
	3640	Lime
	3645	Soft lime
	3650'	Lime TOTAL DEPTH
	3618'	PLUGGED BACK TOTAL DEPTH (PB with 24 sac cement)



PLUGGING
 FILE SEC 13 T 20 R 15 W
 BOOK PAGE 145 LINE 7