

Carlock & Dufton
L. Renollet No. 2.

36-20-8W
W₃ SE₄

15.159.05040.0060
Rice County, Kansas


Contractor: Gerbrand-Pulse Oil & Drlg. Co.

Comm: 1-4-40
Comp: 2-1-40

CASING RECORD

10', 40#, 127' 7"
Cemented 125 sacks cement.
5 1/8", 17#, 8 Thd. Seamless
casing, 3317'
Cemented 75 sacks cement.

| | |
|-----------------------|-----------|
| Surface sand | 125 |
| shale & shells | 805 |
| shale | 1020 |
| lime | 1180 |
| broken lime | 1290 |
| sandy lime | 1325 |
| lime | 1395 |
| sand | 1418 |
| lime | 1575 |
| broken lime | 1640 |
| shale | 1670 |
| broken lime & Shale | 1745 |
| broken lime | 1940 |
| shale & shells | 2160 |
| broken lime | 2195 |
| broken lime & shale | 2330 |
| broken lime | 2370 |
| lime | 2382 |
| soft shale & shells | 2430 |
| shale | 2450 |
| broken lime | 2475 |
| lime | 2550 |
| hard lime | 2565 |
| soft white lime | 2600 |
| hard lime | 2770 |
| broken lime & shale | 2930 |
| lime | 2970 |
| broken lime and shale | 3020 |
| lime | 3060 |
| shale & lime | 3100 |
| shale | 3125 |
| lime and shale | 3170 |
| lime | 3260 |
| lime and shale | 3316 |
| various colored shale | 3319 |
| conglomerate | 3327 T.D. |



PLUGGING
FILE 36-20-8W
BOOK PAGE 133 LINE 34