

5-5-88

To: 1 070542  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION W/2  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-145-20,190-0000  
NE NW, SEC. 36, T. 20 S, R. 16 W/EX  
4620 feet from S section line  
3630 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 5692  
Operator: Fina Oil & Chemical Company  
Name &  
Address 1601 N.W. Expressway, Suite 900  
Oklahoma City, OK 73118

Lease Name Franklin Well # 1-36  
County Pawnee 122.69  
Well Total Depth 3775 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 1030

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Fina Oil & Chemical Company License Number 5692  
Address 1601 N.W. Expressway, Suite 900, Oklahoma City, OK 73118

Company to plug at: Hour: 11 a.m. Day: 5 Month: 5 Year: 19 88

Plugging proposal received from Mark Brin  
(company name) Fina Oil & Chemical Company

RECEIVED 13-483-3741  
STATE CORPORATION COMMISSION

were: 5 1/2" at 3769' Open hole 3767-75'  
1st plug pump 4 sx hulls and 200 sx ATL cement.

MAY 13 1988

CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by Duane Rankin  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 12 p.m. Day: 5 Month: 5 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug pumped 400 lbs. hulls and 128 sx ATL cement. Maximum pressure  
Backside would not take. Maximum pressure 450 psi and shut in 450 psi.  
950 psi and shut in 500 psi.

Remarks: Use ATL cement by Allied. No casing recovery.  
(If additional description is necessary, use BACK of this form.)

INVOICED (If a meter is used, observe this plugging.)

Signed Dan Anderson  
(TECHNICIAN)

DATE 5-17-88  
INV. NO. 20635 AUG 3 1988  
5-5