

To: 1 070413  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 097-21,245 - 0000  
C SE SW, SEC. 25, T 28 S, R 19 W/E  
660 feet from S section line  
3300 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5118

Lease Name Heinze Well # 1

Operator: TGT Petroleum Corporation  
Name & Address 209 East William  
Wichita, KS 67202

County Kiowa 162.83  
Well Total Depth 5010 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 419

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Abercrombie Drilling, Inc. License Number 5422

Address 801 Union Center, Wichita, KS 67202

Company to plug at: Hour: 5 p.m. Day: 11 Month: 9 Year: 19 87

Plugging proposal received from Harvey Moore

(company name) Abercrombie Drilling, Inc. (phone) 316-793-8186

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2281'GL  
Anhydrite 1221-35'

1st plug at 1235' with 50 sx cement, 2nd plug at 460' with 50 sx cement,

3rd plug at 40-0' with 10 sx cement, 4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Paul Luthi  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 7:30 p.m. Day: 11 Month: 9 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 1235' with 50 sx cement,

2nd plug at 460' with 50 sx cement,

3rd plug at 40-0' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
(I did not) observe this plugging.

DATE 9-17-87

Signed Dan Goodson  
(TECHNICIAN)

INV. NO. 18148

9-15-87  
RECEIVED  
COMMISSION  
SEP 15 1987  
Wichita, Kansas

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date... 8... 15... 87... month day year

API Number 15- 097-21,245

OPERATOR: License # 5118... Name TGT. Petroleum Corp... Address 209 E. William... City/State/Zip Wichita, Ks. 67202... Contact Person B. Lynn Herrington... Phone 262-6489

C... SE... SW... Sec. 25... Twp. 28... S... Rg. 19... Ft. from South Line of Section 660... Ft. from East Line of Section 3300

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5422... Name Abercrombie Drilling, Inc... City/State Wichita, Ks

Nearest lease or unit boundary line 660... feet County Kiowa... Lease Name Heinze... Well # 1... Ground surface elevation 7... feet MSL

Well Drilled For: X Oil Storage Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl X Wildcat Cable

Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Depth to bottom of fresh water 170'... Depth to bottom of usable water 250'...

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

Surface pipe by Alternate 1 X 2... Surface pipe planned to be set 400... Conductor pipe required... Projected Total Depth 4950... Formation Mississippi

I certify that well will comply with K.S.A. 55-101, et seq, plus eventually plugging hole to KCC specifications. Date 6-25-87... Signature of Operator or Agent B. Lynn Herrington Title Executive Vice-President

For KCC Use: Conductor Pipe Required... feet; Minimum Surface Pipe Required 320... feet per Alt. 1 X This Authorization Expires 12-30-87... Approved By 6-30-87

Spud 9-30-87-31-89 405 85/8 Halliburton WU

C... SE... SW... Sec. 25... Twp. 28... S... Rg. 19... East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep 1200... or formation with 50... feet of 60-40 Posmix 2nd plug @ ft. deep 750... or formation with 50... feet of 3rd plug @ ft. deep 480... or formation with 50... feet of 4th plug @ ft. deep 40... or formation with 10... feet of 5th plug @ ft. deep... or formation with... feet of

(2) Rathole to surface minus 5 feet (b) Mousehole to surface minus 5 feet

Form with handwritten entries: PUSHER Harvey Thorne, TD 5010' FORMATION MISS, SURFACE PIPE 4 3/4" @ 419', ANHYDRITE 12-21-87 ELEVATION 2281.5', STARTING TIME & DATE 9-11-87 5:00 PM, COMPLETION TIME & DATE 7:30 PM, 1st PLUG @ 1235 FT. W/ 50 SX, 2nd PLUG @ 460 FT. W/ 50 SX, 3rd PLUG @ 40-0 FT. W/ 10 SX, 4th PLUG @ FT. W/ SX, RAT HOLE CIRCULATED W/ 15 SX, MOUSE HOLE CIRCULATED W/ 10 SX, WATER WELL PLUGGED W/ 1/2" water well 6/27/80 w/ 2 1/2" cement, CEMENT COMPANY Halliburton, TECHNICIAN D. G. C. OK RL

RECEIVED SEP 15 1987 CONSERVATION DIVISION Wichita, Kansas