

*R*

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. 46-14

LOCATION SW-SF-SW

SEC. 31 TWP. 26 RGE. 15-W

Dry Hole \_\_\_\_\_ Abandoned Oil Well X Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of: .

Well No. 3 Lease Houdyshell

Operator Anderson Pritchard Oil Co. Address Box # 142 - G. Reed - Kans.

Field \_\_\_\_\_ County Barton

Total Depth 3885 Feet.

(Describe briefly the manner in which the well was plugged)

Surface Pipe 8 1/2 - 1010 ft. Circulated with cement  
5 1/2 casing set at 3812 ft - 175 sacks of cement.  
Plugged back to 3745 ft with Lalle Mills Class 9 sand.  
Runned 15 sacks of cement at 3745 ft. Shot off &  
pulled the 5 1/2 casing - Runned in 30 sacks of heavy  
lead - Plus 200 sacks of cement - filling hole  
from 650 ft to the surface with cement -  
Runned in by - Globe Oil Well Cementing Co  
Boeber Casing Pulling Co. Plugging Contractors

10-4-52

C. H. Stovall  
District Conservation Agent

RECEIVED  
STATE CORPORATION COMMISSION

Date 10-2-52

OCT - 4 1952

CONSERVATION DIVISION  
Wichita, Kansas

**PLUGGING**  
FILE SEC 31 T 26 R 15W  
BOOK PAGE 46 LINE 14