

DISTRICT CONSERVATION AGENT'S REPORT

Q

TO:

State Corporation Commission
Conservation Division
800 Bitting Building
Wichita, Kansas

FILE NO. 84-41

LOCATION SE-SE-21W

SEC. 19 TWP. 20 RGE. 13-W

Dry Hole X Abandoned Oil Well _____ Abandoned Gas Well _____

I have today completed supervision of plugging of:

Well No. 1 Lease Mueckley

Operator Grayhol Contracting Corp. Address 423 Peter Blvd. Wichita-Kans

Field _____ County Barton

Total Depth 3357 Feet.

(Describe briefly the manner in which the well was plugged)

*Surface Pipe 8 3/4 - 222 ft - Circulated with cement.
5/8 casing set at 3529 ft - 45 sacks of cement - Jam Wells
Plug at 3450 ft - sand to 3425 ft - Pumped 5 sacks of
cement at 3425 ft - Shot off & pulled the 5/8 casing -
Pumped in 60 lbs of heavy mud Plug & 100 sacks
of cement - filling hole down 300 ft to the surface
with cement - Pumped in by Globe Oil Well Cementing Co.
The West Supply Co - Plugging Contractors*

PLUGGING
FILE SEC. 29 T. 20 R. 13W
BOOK PAGE 84 LINE 41

RECEIVED
STATE CORPORATION COMMISSION
APR 2 - 1953
CONSERVATION DIVISION
Wichita, Kansas

C. H. Stouch -
District Conservation Agent
Date 3-29-53