

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
266 N. Main St., Ste. 220  
Wichita, KS 67202-1513

API Well Number: 15-205-26040-00-00  
Spot: NESWNWSW Sec/Twnshp/Rge: 1-28S-13E  
1662 feet from S Section Line, 334 feet from W Section Line  
Lease Name: PRESBYTERY Well #: A-1  
County: WILSON Total Vertical Depth: 1468 feet

Operator License No.: 33539  
Op Name: CHEROKEE WELLS LLC  
Address: P.O. BOX 296  
FREDONIA, KS 66736

| String | Size  | Depth (ft) | Pulled (ft) | Comments |
|--------|-------|------------|-------------|----------|
| PROD   | 4.5   | 1455       |             | 165 SX   |
| SURF   | 8.625 | 44         |             | 30 SX    |

Well Type: CM UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 01/25/2018 12:00 PM  
Plug Co. License No.: 99975 Plug Co. Name: COMPANY SERVICING TOOLS  
Proposal Rcvd. from: JEFF MORRIS Company: CHEROKEE WELLS Phone: (620) 378-3650

Proposed Plugging Method: Set 50' 50/50 Poz blend cement plug on TD to approx. 1418'. Fill to approx. 850' with 9# (minimum) bentonite gel, then set 100' cement plug over perforations to approx. 750'. Fill with gel to approx. 150', then cement to surface.

Plugging Proposal Received By: ALAN DUNNING WitnessType: NONE  
Date/Time Plugging Completed: 01/25/2018 12:00 PM KCC Agent: ALAN DUNNING

Actual Plugging Report:

A 2.375 inch cement string was lowered to TD. Pumped gel and then 5 sacks of cement at 1346. The cement string was pulled to 769 ft and 10 sacks of cement pumped. The cement string was pulled to 250 ft and the well pumped full of cement to surface. The cement string was pulled and the well topped off with cement. A total of 40 sacks of portland cement were used to plug well - gel spacers between cement plugs.

Perfs:

| Top | Bot | Thru | Comments |
|-----|-----|------|----------|
| 807 | 810 |      |          |
| 803 | 806 |      |          |

RECEIVED  
KCC DIST # 3  
FEB 21 2018  
CHANUTE, KS

AD

INVOICED  
MAR 02 2018

Remarks:

Plugged through: CSG

District: 03

Signed Alan M. Dunning  
(TECHNICIAN)