FORM CP-2

## State of Kansas



Wichita, Kansas

JOHN CARLIN R. C. LOUX JANE T. ROY PHILLIP R. DICK CAROL J. LARSON Governor Chairman Commissioner Commissioner Executive Secretary

## State Corporation Commission

## CONSERVATION DIVISION

(Oil, Gas and Water)

200 Colorado Derby Building WICHITA, KANSAS 67202

7-9-82

VERBAL PERMIT FORM
(To be filed by Plugging Agent)

15-097-20888

10 Sby of Coment in 1 at holo. The Coment was was  10 Job Poss with at gell + 3% C.C. The plugging  was accomplished by Alled Cementing  Very truly yours,  STATE CORPORATION COMMISSION  JUL 201982  Conservation Division Agent	Dear Sir:
date requested permission to plug the following described well:  Operator's Full: Name: Inalcon Cyploration Co.  Complete Address: /5-31 KS B-T Blog dutin 5-31 Machita Many, bo 7-20-2  Lease Name: Well S. Well No. /  Location: C-SW-NW Sec. 6 Twp. 30 Rge. 19 (E) (VB)  County: Riourn Total Depth: 5-200  Abendoned Oil Well Gas Well Input Well SWD Well DEA CONTROL Was instructed to plug the well as follows:  At plug at 1280 with 5 oshy of cement. Influe 40 to 60  On Jolid Bridge with 10864 of cement. Then Circulated 10 Aby of Cement was 1 as follows:  A for was instructed to plug the well as follows:  A following at 1280 with 10864 of cement. Influe Circulated 10 Aby of Cement was 1 as follows.  A following with 23 gell + 33 C.C. The plugging was accomplished by allied Cementing  Very truly yours,  RECEIVED  STATE COHPORATION COMMISSION  JUL 20 1982  Conservation Division Agent	Mr. Jim Service of Santa Free Vrilletias this
Lease Name: Wells. Well No.  Location: C-SW-NW Sec. 6 Twp. 30 Rge. 19 (E) (D)  County: Mirror Total Depth: 5200  Abandoned Oil Well Gas Well Input Well SWD Well DEAL  Other well as hereafter indicated:  Mr. Location was instructed to plug the well as follows:  In foliage at 1280 with, 5 only of cament. Inspling at 540 with 35 shape of cament. In plug 10 to 0  Day foliage with 10 of gent of cament. Then Circulated 10 shape of Cament in rat hole. The Cament was stated for the Cament	
Lease Name: Wells.  Location: C-SW-NW Sec. 6 Twp. 30 Rge. 19 (E) (D)  County: Reserve Total Depth: 5200  Abandoned Oil Well Gas Well Input Well SWD Well D&A (  Other well as hereafter indicated:  Mr. Serve was instructed to plug the well as follows:  Styping at 1280 with, 50 Aby of Coment, Indepthys of Sure of Solid Solidal with 10 Aby of Coment. Then Curvulated to Aby of Coment was was instructed to plug the well as follows:  Styping at 1280 with 10 Aby of Coment. Then Curvulated to Aby of Coment was was reported with 27 gell + 37 C.C. The plugging was acromplished by Ullich Comenting  Very truly yours,  STATE CORPORATION COMMISSION  JUL 20 1982  Conservation Division Agent	Operator's Full Name: Fralcon Epploration Co.
Lease Name: Wells.  Location: C-SW-NW Sec. 6 Twp. 30 Rge. 19 (E) (D)  County: Reserve Total Depth: 5200  Abandoned Oil Well Gas Well Input Well SWD Well D&A (  Other well as hereafter indicated:  Mr. Serve was instructed to plug the well as follows:  Styping at 1280 with, 50 Aby of Coment, Indepthys of Sure of Solid Solidal with 10 Aby of Coment. Then Curvulated to Aby of Coment was was instructed to plug the well as follows:  Styping at 1280 with 10 Aby of Coment. Then Curvulated to Aby of Coment was was reported with 27 gell + 37 C.C. The plugging was acromplished by Ullich Comenting  Very truly yours,  STATE CORPORATION COMMISSION  JUL 20 1982  Conservation Division Agent	Complete Address: 1531, KS B-T Bllg Suite 1531 Wehite Hours 67202
County: Reserved Total Depth: 5200  Abandoned Oil Well Gas Well Input Well SWD Well DSA Cother well as hereafter indicated:  Mr. Server & was instructed to plug the well as follows:  -st plug at 1280 with 50 shy of cement Independent of State of Consent Indicated  on solid bridge with 10 shy of cement. Then Circulated  10 shy of Cement in rat hole. The Cement was  10 so Poss mix with 27 gell + 37 C.C. The plugging  was accomplished by allied Cementing  Very truly yours,  STATE CORPORATION COMMISSION  JUL 2 0 1982  Conservation Division Agent	
Abandoned Oil Well Gas Well Input Well SWD Well DSA Content well as hereafter indicated:  Mr. Sexue's a was instructed to plug the well as follows:  At plug at 1280 with, 50 shy of cement. Indeplug at 540 with, 35 shep of cement. I all plug 40 to 0  On solid bridge with 10 shy of cement. Then circulated 10 shy of cement in 1 at hole. The Coment was was togo Poss may with D. gell + 32 c.C. The plugging was accomplished by Alkiel Cementing  Very truly yours,  STATE CORPORATION COMMISSION  JUL 201982  Other Well SWD Well DSA Conservation Division Agent	Location: C-SW-NW Sec. 6 Twp. 30 Rge. 19 (E) (W)
Other well as hereafter indicated:  Mr. Lexice was instructed to plug the well as follows:  At plug at 1280 with, 50 Aby of Cement, Indeplug at 540 with, 35 Aby of rement, 3-10 plug 40 to 0'  On solid bridge with 10 Aby of cement. Then Circulated 10 Aby of Cement in rat hole, The Coment was was to 50 Poss min with 27 gell + 3% C.C. The plugging was accomplished by Allied Cementing  Very truly yours,  STATE CORPORATION COMMISSION  JUL 20 1982  October varion Division Agent	County: Rescues Total Depth: 5200'
was instructed to plug the well as follows:    St plug at 1280 with, 50 Aby of Coment. Indeptug  at 540 with 35 Aby of conent. In plug 40 to 0'  on solid bridge with, 10 Aby of conent. Then Circulated  10 Aby of Coment in rat hole. The Coment was was  10 Aby of Coment in rat hole. The Coment was was  10 Aby of Coment in rat hole. The Coment was  10 Aby of Coment in rat hole. The Coment was  10 Aby of Coment in rat hole. The Coment was  10 Aby of Coment in rat hole. The Coment was  10 Aby of Coment in Commission  Very truly yours,  STATE CORPORATION COMMISSION  JUL 20 1982  Outservation Division Agent	Abandoned Oil Well Gas Well Input Well SWD Well D&A
1 st plug at 1280 with 5 odby of cement. Indeplug at 540' with 35 shep of pencent. I al plug 40'to 0'  on solid bridge with 10 she of cement. Then circulated  10 shep of cement in 1 at hole. The Coment used was  50,50 Poss min with 27 gell + 37 C.C. The plugging  was accomplished by Allied cementing  Very truly yours,  STATE CORPORATION COMMISSION  JUL 20 1982  Taul A. Seither  Conservation Division Agent	Other well as hereafter indicated:
on folid bridge with 10 the of coment. Then Circulated 10 they of Coment in rat holo. The Coment used was to 50 Poss my with 27, gell + 3% C.C. The phyging was accomplished by Allied Comenting  Very truly yours,  STATE CORPORATION COMMISSION  JUL 201982  Conservation Division Agent	Mr. <u>ferrice</u> was instructed to plug the well as follows:
on solid bridge with 10 she of cament. Then circulated 10 she of coment in rat holo. The Coment used was to 50 to Poss mily with 27, gell + 3% C.C. The plugging was accomplished by Allied Comenting  Very truly yours,  STATE CORPORATION COMMISSION  JUL 201982  Onservation Division Agent	1 st plug at 1280 with 50 Shy of Cement Ind plug
on solid bridge with 10 she of cament. Then circulated 10 she of coment in rat holo. The Coment used was to 50 to Poss mily with 27, gell + 3% C.C. The plugging was accomplished by Allied Comenting  Very truly yours,  STATE CORPORATION COMMISSION  JUL 201982  Onservation Division Agent	at 540' with 35 Apy of sement 3 rd plue 40 tho!
Very truly yours,  RECEIVED  STATE CORPORATION COMMISSION  JUL 201982  Very truly yours,  Conservation Division Agent	on solid bridge with 10 fby of cement. Then circulated
Very truly yours,  RECEIVED  STATE CORPORATION COMMISSION  JUL 201982  Very truly yours,  Conservation Division Agent	10 Sby of coment in rat holo, The Coment used was
Was accomplished by Allied Cementing  Very truly yours,  STATE CORPORATION COMMISSION  JUL 2 0 1982  Very truly yours,  Conservation Division Agent	
RECEIVED STATE CORPORATION COMMISSION  JUL 2 0 1982  Very truly yours,  Conservation Division Agent	was accomplished by Allied cementing
JUL 2 0 1982  JUL 2 0 1982  Conservation Division Agent	
JUL 2 0 1982 Conservation Division Agent	RECEIVED STATE CORPORATION COMMISSION
Conservation Division Agent	
CONSERVATION DIVISION	Conservation Division Agent  CONSERVATION DIVISION